6" DOWNLIGHT 14.5W TITANIUM CRI^{SP} LED SERIES

GREENCREATIVE

ENERGY STAR

HIGH CRI
LED TECHNOLOGY

CRI^{SP}

CLICK DESIGN

14.5W REPLACES

85W Inc.

80% Energy Savings

$208 Savings per lamp*

- **Innovative CLICK design**
- **Fits most 4" J-boxes and 5-6" recessed housings**
- **Installs in just minutes - no rewiring**
- **Exceptional color rendering CRI 90**
- **Richer reds and natural skin tones (R9 60, R13 90)**
- **Tight LED binning for consistent CCT across all lamps**

40,000 H	DIMMABLE	66 LPW EFFICACY
5 YR WARRANTY	90 CRI (Ra)	SEMI DIRECTIONAL

c(UL)us LISTED   FC   lighting facts LED Product Partner   LM 79   LM 80   TM 21   IES

DOWNLIGHT PRODUCT FEATURES

DUAL INSTALLATION:

| 4" J-BOX FLUSHMOUNT	4" CAN RECESSED	5-6" CAN RECESSED
ACCESSORIES INCLUDED:	ACCESSORIES SOLD SEPARATELY:	ACCESSORIES SOLD SEPARATELY:
• Attach mounting bracket to J-box • Click downlight into mounting bracket	• Connect E26 adapter to the LED adapter • Insert mounting clips and push downlight up until flush with ceiling	• Connect E26 adapter to the LED adapter • Squeeze mounting springs and push downlight up until flush with ceiling
Mounting Bracket J-Box Screws	E26 Adapter LED Adapter	E26 Adapter LED Adapter
Wire Nuts LED Adapter	Mounting Bracket Mounting Clips	Mounting Springs

Ref:#DS175-CLICK-6-14.5W-290118

APPLICATIONS

General Lighting

RECESSED LIGHTING

Recessed Lighting

Accent Lighting

SPECIFICATIONS

Product	40842	40843	40847
Model	14.5SMDL6DIM/927	14.5SMDL6DIM/930	14.5SMDL6DIM/840
Type	6" SMDL	6" SMDL	6" SMDL
Base	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)
Power (W)	14.5	14.5	14.5
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra)	90	90	80
Typical lumens (lm)	920	950	1050
Efficacy (LPW)	63	66	72
Beam Angle	110°	110°	110°
Dimmable	Yes***	Yes***	Yes***
Housing Compatibility	4" J-box / Most 5-6" housing	4" J-box / Most 5-6" housing	4" J-box / Most 5-6" housing
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	40,000	40,000	40,000
Dia. x MOL	7.32"x1.30" (186x33mm)	7.32"x1.30" (186x33mm)	7.32"x1.30" (186x33mm)
Weight (lb. / g)	0.45lb. / 204g	0.45lb. / 204g	0.45lb. / 204g

ACCESSORIES (SOLD SEPARATELY)

Product	57973	57974
Model	SMDL4/ACC	SMDL6/ACC
Type	4'' Can Installation Accessories	5-6'' Can Installation Accessories

* Savings per lamp based on $0.11 / kw energy cost, 12 hrs / day lamp usage, $4 incandescent with 1000-hr lifetime, $25 LED with 40,000-hr lifetime
** Suitable for closet installation when installed in accordance with NEC requirements

*** List of tested dimmer switches available on website
**** Suitable for damp locations. Not for use where directly exposed to weather or water