

# 6" DOWNLIGHT 11W TITANIUM CRI<sup>SP</sup> LED SERIES



**CRISP**



11W REPLACES



**65W Inc.**

80% Energy Savings

**\$193 Savings per lamp\***

- ⌚ Innovative CLICK design
- ⌚ Fits most 4" J-boxes and 5-6" recessed housings
- ⌚ Installs in just minutes - no rewiring
- ⌚ Wet location rated
- ⌚ Exceptional color rendering CRI 90
- ⌚ Richer reds and natural skin tones (R9 60, R13 90)



40,000 H



DIMMABLE



65 LPW EFFICACY



5 YR WARRANTY



CRI (Ra) 90



WET LOCATION




## DOWNLIGHT PRODUCT FEATURES

### DUAL INSTALLATION:

#### 4" J-BOX FLUSHMOUNT

ACCESSORIES INCLUDED:



- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket



J-Box Screws




Wire Nuts



LED Adapter

#### 4" CAN RECESSED

ACCESSORIES SOLD SEPARATELY:




- Connect E26 adapter to the LED adapter
- Insert mounting clips and push downlight up until flush with ceiling



E26 Adapter



LED Adapter




Mounting Bracket



Mounting Clips

#### 5-6" CAN RECESSED

ACCESSORIES SOLD SEPARATELY:



- Connect E26 adapter to the LED adapter
- Squeeze mounting springs and push downlight up until flush with ceiling



E26 Adapter



LED Adapter



Mounting Springs

# 6" DOWNLIGHT 11W TITANIUM CRISP<sup>SP</sup> LED SERIES



## APPLICATIONS

### General Lighting



### Recessed Lighting



### Accent Lighting



## SPECIFICATIONS

Product Model	58101 11SMDL6DIM/927	58102 11SMDL6DIM/930	58103 11SMDL6DIM/940
<b>Type</b>	6" SMDL	6" SMDL	6" SMDL
<b>Base</b>	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)
<b>Power (W)</b>	11	11	11
<b>Voltage - Frequency</b>	120V 60Hz	120V 60Hz	120V 60Hz
<b>Color Temp. (ANSI)</b>	Soft White 2700K	Warm White 3000K	Cool White 4000K
<b>CRI (Ra)</b>	90	90	90
<b>Typical lumens (lm)</b>	680	720	750
<b>Efficacy (LPW)</b>	62	65	68
<b>Beam Angle</b>	110°	110°	110°
<b>Dimmable</b>	Yes**	Yes**	Yes**
<b>Housing Compatibility</b>	4" J-box / Most 5-6" housing	4" J-box / Most 5-6" housing	4" J-box / Most 5-6" housing
<b>Power Factor</b>	0.9	0.9	0.9
<b>Rated Lifetime - L70 (hrs.)</b>	40,000	40,000	40,000
<b>Dia. x MOL</b>	7.32"x1.30" (186x33mm)	7.32"x1.30" (186x33mm)	7.32"x1.30" (186x33mm)
<b>Weight (lb. / g)</b>	0.45lb. / 204g	0.45lb. / 204g	0.45lb. / 204g

## ACCESSORIES (SOLD SEPARATELY)

Product Model	57973 SMDL4/ACC	57974 SMDL6/ACC
<b>Type</b>	4" Can Installation Accessories	5-6" Can Installation Accessories

\* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$25 LED with 40,000-hr lifetime  
 \*\* Suitable for closet installation when installed in accordance with NEC requirements

\*\*\* List of tested dimmer switches available on website