


Brass Bullyte (B1) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:

Ordering Guide

Example: B1 N L

Product Code	B1	Brass Bullyte
Finish	N OB	Natural Brass Oiled Brass
Shroud	L	Long Shroud



Specifications

HOUSING:

Die-cast brass. Fully rotatable shroud, gasketed die-cast brass. Fully-adjustable swivel arm with vibration-proof locking teeth. 1/2" NPS male threads to screw onto accessory mounting stake or junction box, sold separately. Gasketing is silicone. Fasteners are 300 series stainless steel.

FINISH:

Natural Brass (N) is as-cast and tumble polished. HADCO's Oiled Brass (OB) is chemically dipped to achieve a dark pre-aged patina finish and the appearance will vary between production runs. Finishes will continue to patina over time making each fixture unique.

OPTICAL ASSEMBLY:

Clear tempered glass affixed at 10° angle for natural cleaning.

LAMPING:

100W maximum PAR20/R20 medium base lamp. Lamp is not included. Lower wattage lamps are acceptable.

ELECTRICAL ASSEMBLY:

4kv rated porcelain medium base. Nickel-plated screw shell with center contact. Fixture is pre-wired with 18 AWG black, white, and ground wires.

BALLAST:

Must order inground (IBH) or above ground (ABH) ballast housing separately.

WARRANTY:

Lifetime limited warranty.

CERTIFICATIONS:

ETL listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards.

Width:

3 7/8" (98mm)

Length:

8 3/16" (208mm)

Max. Weight:

4.46 lb.