

RECESSED REMODEL ADJUSTABLE

PRODUCT DESCRIPTION

Recessed adjustable MR16 remodel luminaire with $3\frac{1}{4}$ " aperture. Fixture has 50° visual cutoff to lamp and lamp image. Low profile non-IC housing is for use in non-insulated areas, or where insulation is spaced at least 3" from housing. Installs quickly and securely with patented (US Patent 7,191,993) push-pull cable system through ceiling opening.

PRODUCT SPECIFICATIONS

Trims Style Utilizes torsion spring retention for tight, secure fit to ceiling • Trim ring features beveled knife edge for clean ceiling interface.

Lens Lampholder accommodates up to three (3) 2" captive accessory lenses • Supplied with stippled clear uniformity lens.

Socket Ceramic bi-pin socket with double blade nickel alloy contacts • Aluminum heat shield.

Lamp One 50W MR16 lamp max. (See trim for max. lamp rating)

Adjustability Optimized lamp beam optics ensures maximum light output and low brightness at any angle • 361° rotation (350° with mechanism, up to 18° additional with rotation of housing assembly) and 35° tilt hot aiming • Black adjustment mechanism preserves dark aperture.

Transformer 120V thermally protected magnetic transformer is servicable from below ceiling • GE LET 75, 120V high efficiency (>95%), high power factor electronic transformer also available.

Dimming May be dimmed using dimmers specifically designed for low voltage magnetic or electronic transformers; consult factory or dimmer manufacturer for additional information.

Codes/Labels UL and cUL listed for through-branch wiring, damp locations (wet location with approved trims) • Product thermally protected • Union made.

Patented (US Patent 7, 191, 993) " Push-Pull" Cable

System Allows rapid installation without tools or loose parts
Template included for accurate ceiling cutout

Housing accommodates ceiling thickness from 3/8" to 2" without altering photometrics
Fits 2 x 6 construction.

Junction Box Rated for 4 No. 12 AWG 90° C through branch circuit conductors and includes (3) ½", and (2) Non-metallic sheathed cable knock-outs • Push-in electrical connectors for field connections.

Housing/Mounting Frame Galvanized steel plaster frame. Housing painted black for visually dark interior • Packaged for ease of rapid installation. 3-1/4" APERTURE Non-IC Rated, MR16 Halogen **TC43NR**

Project:


Fixture Type:

Location:

Contact/Phone:



DIMENSIONS



4 7/16" CEILING CUTOUT

Ordering Information Housing, trim and accessories each ordered separately

Housing	Transformer	Optical Accessories			
TC43NR Blank E1	Low Voltage 120V Magnetic Low Voltage 120V Electronic GE LET 75		Description Med. Pink Color Filter Warm Red Color Filter Daylight Blue Color Filter Med. Blue Color Filter Med. Green Color Filter Red Dichroic Lens Med. Green Dichroic Lens Med. Blue Dichroic Lens pecify catalog number.	Cat. # T7405 T7406 T7411 T7416 T7420 T7422 T7477 T7478 T7459BL	Description Yellow Dichroic Lens Magenta Dichroic Lens Blue Green Dichroic Lens Daylight Blue Correction Lens Diffuse Spread Lens UV Filter Lens Prismatic Lens Linear Spread Lens Hexcell Louver

Product specifications subject to change without notice.





3 1/4" RECESSED REMODEL ADJUSTABLE TC43NR, MR16 Halogen

Trim Selection

	Cat. No.	Description	Lamp Ratir
Deep Downli	ight Cone 437NB-ABZ 437NB-SC 437NB-WH 437NC-WH 437NHZ-SC 437NHZ-WH 437NHZ-WH 437NWHZ-ABZ 437NWHZ-WH	Black Alzak® Cone Black Alzak® Cone Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16
Deep Downli	ight Baffle 434NB-ABZ 434NB-SC 434NB-WH 434NW-WH	Black Baffle Black Baffle Black Baffle White Baffle	50W MR16
Downlight 1	1/4" Pinhole 4337N-ABZ 4337N-SC 4337N-WH	Black Alzak® Reflector Black Alzak® Reflector Black Alzak® Reflector	50W MR16
LENSED (Trii	m Ring Catalo	a # Shown)	
Downlight Le	-	Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16
	ensed Trim 432NB-WH 432NC-WH 432NHZ-SC 432NHZ-WH 432NWHZ-ABZ 432NWHZ-WH	Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone	
Downlight Le	ensed Trim 432NB-WH 432NC-WH 432NHZ-SC 432NHZ-WH 432NWHZ-ABZ 432NWHZ-WH 431NB-WH 431NC-WH 431NHZ-SC 431NHZ-WH 431NWHZ-ABZ	Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16

Trim Ring Finish: ABZ - Classic Aged Bronze, BL - Black, SC - Satin Chrome, WH - White.

ADJUSTABLE ACCENT (Trim Ring Catalog # Shown)					
	Cat. No.	Description	Lamp Rating		
Angle-Cut Co	DNE 438NB-ABZ 438NB-SC 438NB-WH 438NC-WH 438NHZ-SC 438NHZ-WH 438NWHZ-ABZ 438NWHZ-WH	Black Alzak® Cone Black Alzak® Cone Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16		
20° Angle-C	ut Cone 430NB-WH 430NC-WH 430NHZ-SC 430NHZ-WH 430NWHZ-ABZ 430NWHZ-WH	Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16		
Slot Angle-C	ut Cone 436NB-ABZ 436NB-SC 436NB-WH 436NC-WH 436NHZ-SC 436NHZ-WH 436NWHZ-ABZ 436NWHZ-WH	Black Alzak® Cone Black Alzak® Cone Black Alzak® Cone Clear Alzak® Cone Haze Alzak® Cone Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone	50W MR16		
Angle-Cut Bo	affle 435NB-ABZ 435NB-SC 435NB-WH 435NW-WH	Black Baffle Black Baffle Black Baffle White Baffle	50W MR16		
Adjustable 1	l 1/4" Pinhole 433N-ABZ 433N-SC 433N-WH	Black Alzak® Reflector Black Alzak® Reflector Black Alzak® Reflector	50W MR16		
Adjustable 1	I 3/4″ Pinhole 4335N-ABZ 4335N-SC 4335N-WH	Black Alzak® Reflector Black Alzak® Reflector Black Alzak® Reflector	50W MR16		
Slot Pinhole	4345N-WH	Black Alzak® Reflector	50W MR16		
WALL WASH (Trim Ring Catalog # Shown)					
Lensed Wall	Wash 439NB-WH	Black Alzak® Cone	50W MR16		



439NC-WH Clear Alzak® Cone 439NHZ-SC Haze Alzak® Cone 439NHZ-WH 439NWHZ-ABZ Haze Alzak® Cone Wheat Haze Alzak® Cone Wheat Haze Alzak® Cone 439NWHZ-WH