



Catalog Number
Notes
Type

Contractor Select™

6RLS

6" LED Surface Mount

The Juno® Basics Series™ 6RLS Surface Mount LED attaches directly to any standard junction box in two simple steps. No recessed housing required. Use it as a downlight or a sconce. Super-thin fixture fits flush with any flat surface, mimicking the appearance of a recessed downlight. All in one design includes LED light engine, lens and trim. They are ENERGY STAR® certified, can be used to comply with Title 24, JA8 high efficacy light source requirements, Wet Location listed and include a 5-year limited warranty.



FEATURES:

- Installs directly onto industry standard junction boxes and round mudrings
- 3000K color temperatures, 90+ CRI
- Dimmable with most standard incandescent and low voltage dimmers



Catalog Number	UPC	Description	Replaces Up To	Lumens	Input Watts	CCT	CRI	Voltage	Finish	Dimming Protocol	Pallet qty.
6RLS G2 07LM 30K 90CRI 120 FRPC WH M6	190887659061	6" Basic Series™ LED Surface Mount Fixture	65W Incandescent	700	10	3000K	90	120	White	Forward & Reverse Phase Cut	540
6RLS G2 10LM 30K 90CRI 120 FRPC WH M6	190887659078	6" Basic Series LED Surface Mount Fixture	75W Incandescent	1000	14.5	3000K	90	120	White	Forward & Reverse Phase Cut	540



Specifications

CONSTRUCTION:

Decorative beveled aluminum trim frame with white finish • Diffusing dome lens conceals the LEDs from direct view and provides uniform lens luminance.

LED LIGHT ENGINE:

LED board mounted directly to aluminum housing designed to provide superior thermal management and ensure long life • 3000K LED color temperature • LED's binned for 3-step MacAdam ellipse color consistency • 90 CRI minimum • Accommodates 120 volts AC at 60Hz • Dimmable with most standard incandescent, magnetic low voltage and electronic low voltage dimmers • For a list of compatible dimmers, see [JUNORETROBASICS-DIM](#).

ELECTRICAL CONNECTIONS:

Fixture provided with leads for direct wire connection in j-box • Low profile fixture design is free from external electrical components, so j-box volume and box fill is not compromised • Accessory retrofit kit ships with a medium base socket adapter whip for installation as a retrofit trim into 5" or 6" incandescent housings with medium base sockets.

LIFE:

Rated for 50,000 hours at >70% lumen maintenance.

LABELS:

ENERGY STAR® Certified • Certified to the high efficacy requirements of California T24 • UL listed for US and Canada • Suitable for damp locations • Suitable for wet locations (indoor covered ceilings) when fixture is sealed to ceiling with field applied caulk (see instruction sheet for details).

TESTING:

All reports are based on published industry procedures; field performance may differ from laboratory performance.

JUNCTION BOX MOUNTING:

Installs directly to industry standard junction boxes • Compatible boxes include 3-1/2" and 4" octagon junction boxes (1-1/2" minimum depth), round mud rings with 2-3/4" mounting centers, and 3" & 4" diameter non-metallic boxes • Quick-mount strap and spring securement system provides fast installation of fully assembled fixture to junction box • Suitable for ceiling or wall mount • Suitable for use within closet storage spaces when installed per NEC requirements.

WARRANTY:

5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

