

Reflector Trim	Frame-In Kit - See Individual Frame-In Kit Specification Sheets			
	Incandescent			
	Frame-In Kit	Installation Type	Lamping	Height
<b>1088</b> Matte Black Baffle	1004IC/N	Non-IC	75W PAR30 Sylvania short neck only	7 1/2"
<b>1088WH</b> Matte White Baffle	1004ICR	Non-IC Remodeler		7 1/2"
<b>1088GW</b> Gloss White Baffle	1004IC/N	IC	50W PAR30	7 1/2"
	1004ICR	IC Remodeler		7 1/2"

### Features


- Housing:** Aluminum, .032 (18 ga.) Beveled trim flange.
- Eyeball:** Formed, one piece aluminum, .032 (18 ga.); provides 0° to 30° vertical adjustment; non-yellowing, scratch resistant finish.
- Frame-In Kit:** (1004IC standard frame shown). Other frame shown on the right. See Frame-In Kit specification sheets for more details.

### Labels

UL Listed. Suitable for Damp Locations.


Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

Lightolier a Genlyte company www.lightolier.com  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2012 Genlyte Group LLC • E0112



Lighting Performance Data													
DISTANCE 0' 1' 2' 3' 4' 5' 6'	Narrow				Medium				Wide				
	50W PAR30 NSP (T-H)		75W PAR30 NSP (T-H)		50W PAR30 NFL (T-H)		75W PAR30 NFL (T-H)		50W PAR30 FL (T-H)		75W PAR30 FL (T-H)		
FOOTCANDLES (On Beam Center At 6') ▶	181		291		49		83		31		50		
BEAM SPREAD (To 50% Max. CP)	12"		12"		32"		32"		42"		42"		
MAX. CANDLEPOWER (Candelas)	6,500		10,500		1,750		3,000		1,100		1,800		
RATED LIFE (Hours)	2,000		2,000		2,000		2,000		2,000		2,000		
<b>0° AIMING ANGLE</b> Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
		6'	181	1.3'	1.3'	8'	164	1.7'	1.7'	4'	109	2.3'	2.3'
		8'	102	1.7'	1.7'	12'	73	2.5'	2.5'	6'	49	3.4'	3.4'
		10'	65	2.1'	2.1'	16'	41	3.4'	3.4'	8'	27	4.6'	4.6'
		12'	45	2.5'	2.5'	20'	26	4.2'	4.2'	10'	17	5.7'	5.7'
		6'	83	3.4'	3.4'	3'	122	2.3'	2.3'	4'	113	3.1'	3.1'
		8'	47	4.6'	4.6'	5'	44	3.8'	3.8'	6'	50	4.6'	4.6'
		10'	30	5.7'	5.7'	7'	22	5.4'	5.4'	8'	28	6.1'	6.1'
		12'	21	6.9'	6.9'	9'	14	6.9'	6.9'	10'	18	7.7'	7.7'
<b>30° AIMING ANGLE</b> Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
		5'	169	1.4'	1.2'	7'	139	2.0'	1.7'	3'	126	2.4'	2.0'
		7'	86	2.0'	1.7'	10'	68	2.8'	2.4'	5'	45	3.9'	3.3'
		9'	52	2.5'	2.2'	13'	40	3.7'	3.2'	7'	23	5.5'	4.6'
		11'	35	3.1'	2.7'	16'	27	4.5'	3.9'	9'	14	7.1'	6.0'
		5'	78	3.9'	3.3'	3'	79	3.2'	2.7'	3'	130	3.2'	2.7'
		7'	40	5.5'	4.6'	5'	29	5.4'	4.4'	5'	47	5.4'	4.4'
		9'	24	7.1'	6.0'	7'	15	7.5'	6.2'	7'	24	7.5'	6.2'
		11'	16	8.6'	7.3'	9'	9	9.7'	8.0'	9'	14	9.7'	8.0'
<b>30° AIMING ANGLE</b> Illumination on Vertical Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
		2'	203	1.7'	0.8'	3'	146	2.6'	1.3'	1'	219	3.0'	1.1'
		3'	90	2.6'	1.3'	4'	82	3.5'	1.7'	2'	55	6.1'	2.3'
		4'	51	3.5'	1.7'	5'	53	4.3'	2.1'	3'	24	9.1'	3.4'
		5'	33	4.3'	2.1'	6'	36	5.2'	2.5'	4'	14	12.2'	4.6'
		2'	94	6.1'	2.3'	1'	138	5.5'	1.5'	1'	255	5.5'	1.5'
		3'	42	9.1'	3.4'	2'	34	11.0'	3.1'	2'	56	11.0'	3.1'
		4'	23	12.2'	4.6'	3'	15	16.5'	4.6'	3'	25	16.5'	4.6'
		5'	15	15.2'	5.7'	4'	9	22.0'	6.1'	4'	14	22.0'	6.1'

Data are based on bare lamp photometrics.  
 FC is initial footcandles at center of beam. L and W are to the point that the candlepower drops 50% of maximum



### Beam Center Location

Distance D (ft.)	1	2	3	4	5	6	7	8	9	10
Distance C (ft.)	1.7	3.5	5.2	6.9	8.7	10.4	12.1	13.8	15.6	17.3

This chart locates the distance (C) to the center of the light beam for various distances (D) when the lamp is aimed 30° from vertical, the preferred aiming angle for lighting pictures on a wall

**Job Information** **Type:**

Lightolier a Genlyte company www.lightolier.com  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2012 Genlyte Group LLC • E0112