



Reflector Trim	Frame-In Kit
8091CBW White Cone, White Flange 8091CBA Aluminum Cone, White Flange	S6132BU 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam) Dimming Options: S6132B <input type="checkbox"/> CU3 Lightolier PowerSpec 3% Dimming (120/277V) J1LD3 Lutron 5% Dimming (120V) J2LD3 Lutron 5% Dimming (277V) JUM7 Mark 7 Dimming (120/277V) J1MX Mark 10 Dimming (120V) J2MX Mark 10 Dimming (277V) Other dimming product available, please consult factory
	Remodeler Frame-In Kits
	6126BURM 6" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam) 6132BURM 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)

Features

- Reflector:** 16 ga. Die-formed aluminum, Anobrite® finish.
- Socket Cup:** Effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Mounting Frame:** Galvanized steel for dry or plaster ceilings. Accepts other 6" Triple Tube reflectors (see S6132BU Spec Sheet).
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Electronic 120V-277V. UL listed for through branch circuit wiring with max of (8) No. 12AWG, 90°C supply conductors. Outboard-mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Cross Blade Louver:** Die-formed, 16 ga. aluminum, matte white or painted aluminum finish. Accepts lens (consult factory). 50° cutoff to lamp, medium beam. Keyed for orientation.

Electrical

Note: For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

Options and Accessories

Other Louver Finishes Consult Factory

- | | |
|-----------------------|-----------------------|
| Emergency | Add suffix EM* |
| Chicago Plenum | Use 6132BULC |
| Existing/Thk. Ceiling | FA EC6* |
| Emergency Ltg. Kit | FA EM3E* |
| Fuse (Slow Blow) | Add Suffix F |
- *See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA.

Sloped Ceiling Adapters; see Specification Sheet SCA.

IC Frame available; see **C6CFL32** specification sheet.

Labels

UL listed for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2009 Philips Group • B0209

