



| Reflector Trim  | Frame-In Kit  |
|---|---|
| <b>8022 CCLW</b> Comfort Clear™, White Flange<br><b>8022 CCLP</b> Comfort Clear™, Polished Flange<br><b>8022 CCL</b> Comfort Clear™, Molded Trim Ring<br><b>8022</b> <input type="checkbox"/> Add suffix. See options for other finishes.                               | <b>S7126BU</b> 7" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam)<br><b>S7132BU</b> 7" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)<br><b>S7142BU</b> 7" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam)<br><b>Dimming Options:</b><br><b>S7132B</b> <input type="checkbox"/> or <b>S7142B</b> <input type="checkbox"/><br><b>CU3</b> Lightolier PowerSpec 3% Dimming (120/277V) <b>J1LD3</b> Lutron 5% Dimming (120V)<br><b>J2LD3</b> Lutron 5% Dimming (277V) <b>JUM7</b> Mark 7 Dimming (120/277V)<br><b>J1MX</b> Mark 10 Dimming (120V) <b>J2MX</b> Mark 10 Dimming (277V)<br>Other dimming product available, please consult factory |
| <b>Remodeler Frame-In Kits</b>  |   |
| <b>7126BURM</b> 7" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam)<br><b>7132BURM</b> 7" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)<br><b>7142BURM</b> 7" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam) |   |

## Features

- Reflector:** 16 ga. Alzak® aluminum, 50° visual cutoff to lamp and lamp image, medium distribution. Comfort Clear™ low iridescence finish. Self-flanged or flangeless with molded white trim ring (field paintable).
- Socket Cup:** Effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Mounting Frame:** Galvanized steel for dry or plaster ceilings. Accepts other 6" Triple Tube reflectors (see S6132BU Spec Sheet).
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Electronic 120V-277V. UL listed for through branch circuit wiring with max of (8) No. 12 AWG, 90°C supply conductors. Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.

## Electrical

**Note:** Note: For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

## Options and Accessories

| Comfort Clear™ Finishes <sup>1</sup> |            | Other Finishes |           |
|--------------------------------------|------------|----------------|-----------|
| Diffuse                              | <b>CCD</b> | White          | <b>WH</b> |
| Champagne Bronze                     | <b>CCZ</b> | Specular Clear | <b>CL</b> |
| Pewter                               | <b>CPW</b> |                |           |

<sup>1</sup>Specify desired flange. **W** White, **P** Polished, Blank - Molded Ring

## Options and Accessories (continued)

|                               |                                |
|-------------------------------|--------------------------------|
| Emergency Ltg. Kit            | <b>FA EM3E*</b>                |
|                               | <b>FA EM4*</b>                 |
| Fuse (Slow Blow)              | Add suffix <b>F</b>            |
| Existing/Thk. Ceiling         | <b>Plaster Trim Ring CA7FL</b> |
| Emergency                     | Add suffix <b>EM*</b>          |
| Chicago Plenum                | Use 7142, BULC                 |
| *See Spec. Sheets: FAEM, FAEC |                                |

Mounting Bars & Accessories; see Specification Sheet MBA.  
Sloped Ceiling Adapters; see Specification Sheet SCA.

## Labels

UL, CUL, I.B.E.W

Alzak® is a registered trademark of ALCOA

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

