

LINESCAPES WALL

Wall lamp with an efficient highly versatile linear luminous output.
Body in extruded aluminum and opal white polycarbonate diffuser.
Horizontal cantilever wall version supplied with kit for connection
with remote driver.



DRIVER ON BOARD L40 3000K

LAMPING


Source	Linear LED
Total power	19W
Emission	diffused, side emission
Tension	110/240V
Color temperature	3000K
Luminous flux	1125lm
Typ CRI	85
IP class	20
Notes	Side emission, driver on board, 3500K and 4000K available on request, square cover plate included

Codes

LIN LWD 35
LIN LND 35

Structure

white/grey
black



DRIVER ON BOARD L72 2700K

LAMPING


Source	Linear LED
Total power	19W
Emission	diffused, side emission
Tension	emission 19W 1125lm typ cri 85 110/240V
Color temperature	2700K
Luminous flux	1125lm
Typ CRI	85
IP class	20
Notes	Side emission, driver on board, 3500K and 4000K available on request, square cover plate included

Codes

LIN LW2 36
LIN LN2 36

Structure

white/grey
black



DRIVER ON BOARD L72 3000K

LAMPING

Source	Linear LED
Total power	19W
Emission	diffused, side emission
Tension	emission 19W 1125lm typ cri 85 110/240V
Color temperature	3000K
Luminous flux	1125lm
Typ CRI	85
IP class	20
Notes	Side emission, driver on board, 3500K and 4000K available on request, square cover plate included

Codes

LIN LWD 36
LIN LND 36

Structure

white/grey
black

