

NOX-436 4" Onyx Square Retrofit Downlight

Source: LED, 10.5 Watts, 650 Lumens

PRODUCT DESCRIPTION

The Onyx 4" Square Series is suitable for use with most 4" recessed housings. Die-cast aluminum construction provides clean sharp edges. Deep regressed optics and square aperture delivers even and glare-free illumination. Available in multiple color temperatures and 90+ CRI. Onyx square is cULus wet label and ENERGY STAR listed.

FEATURES

- 650 lumens
- High color rendition: 90+ CRI
- 120V / 10.5 Watts max
- 2700K, 3000K and 4000K
- Integral driver
- Dimmable
- Includes medium base socket adaptor for easy retrofitting in 4" recessed housings
- Quick connector is compatible with Nora NHIC-4LMRAT and NHRIC-4LMRAT dedicated LED housings.
- *LED Dedicated housings are required by some codes in recessed can applications or to meet energy rebate program requirements.*
- ENERGY STAR and cULus Wet Label listed

SPECIFICATION

Trim: One piece, die-cast aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Housings: Compatible with most 4" IC and non-IC housings by Nora and others.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

Optics: Nora specified and designed precision-molded lens for optimal lumen output and even distribution. The white polymer lens diffuser evenly distributes the light.

ELECTRICAL

- Voltage:** 120V
Lumens: 650lm
CRI: 90+ CRI
Wattage: 10.5 Watts
Light Source: Samsung LED
Driver: Built-in driver, 104mA
Operating Temp: 0°C to 45°C ambient temperature
Dimming: 5% with electronic low voltage dimmer or 10% with 2-wire dimmer

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.

COMPATIBLE HOUSINGS

- Fire Box**
NFBIC-4LMRAT* 4" ICAT Dedicated LED Fire Box
- New Construction**
NSIC-401QAT 4" ICAT Line Voltage
NS-401QAT 4" AT Line Voltage
NHIC-4G24AT 4" ICAT GU24
NHIC-4LMRAT* 4" ICAT Dedicated LED
NHIC-4LMRAT/277* 4" ICAT Dedicated LED, 277V
NHIC-427LMRAT* 4" ICAT Shallow Dedicated LED
- Remodel**
NSR-404AT 4" AT Line Voltage
NHRIC-4G24AT 4" ICAT GU24
NHRIC-4LMRAT* 4" ICAT Dedicated LED


* Nora LED Dedicated housings are cULus listed for use only with Nora Diamond/Cobalt/Onyx Series LED Retrofits.

LABELS AND LISTINGS

ENERGY STAR Listed
 cULus Wet Listed
 Meets ASTM-E283 Air-Tight requirements
 5 Year / 50,000 Hour Limited Warranty



PRODUCT IMAGES AND DIMENSIONS



Width: 5"
Aperture: 3"
Height: 3-1/8"



NRA-211SM
 Medium Base screw-in socket included for retrofitting into existing Medium Base downlight housings



NRA-212SM
 Socket adapter for use with GU24 base housings

4" Onyx Square LED Retrofit

CAT. NO	COLOR TEMP	FINISH
NOX-436 Square	27 2700K	WW White / White
	30 3000K	
	40 4000K	

Example: **NOX-43640WW** 4" Onyx Square LED Retrofit, 3000K, White finish.