

**ADELPHI Vanity**  
**3-537-xx**

oxygen


FIXTURE TYPE \_\_\_\_\_ LOCATION \_\_\_\_\_  
PROJECT \_\_\_\_\_ DATE \_\_\_\_\_



-24 Satin Nickel



-15 Black



-22 Oiled Bronze



-40 Aged Brass

**LIGHT SOURCE** 1 x 11.7W LED, 3000K, CRI 90  
**LUMINAIRE POWER** 14.1W at 120V  
**RATED LIFE** 60000 hr RL  
**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K  
**LUMEN OUTPUT** Delivered: 1258 lm (LM-79)  
**INPUT VOLTAGE** 120V to 277V AC, 50/60Hz  
**DRIVER OUTPUT** 350mA, 14.7W max power  
**DIMMING** TRIAC and ELV dimming at 120V AC;  
0-10V dimming, 100% to 10% current output


**CONSTRUCTION** Plated Steel and Acrylic

**DIFFUSER** - Matte White Acrylic

**FINISHES** Black (-15), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40)

**MOUNTING** 4" Octagonal J-Box, 4" Square J-Box,  
4" Square J-Box with single device mud ring,  
4" Square J-Box with round mud ring (2.75" center to center mounting)

**STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to  
UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 24.25"  
**H:** 4.75"  
**Ext:** 3.50"  
**M.C:** 2.37" From top of fixture

Order example for standard fixture:

**3-537-24** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120V to 277V

Order example for optional color temperatures: **3-537-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

