REFLEX Wall Sconce

120v: **3-504-xx**



LOCATION _____ FIXTURE TYPE _ PROJECT_ DATE .





-14 Polished Chrome







-24 Satin Nickel

-25 Satin Copper

With optional backplate

LIGHT SOURCE 2 x 7W Max LED GU10 Base (Lamp not included)

LUMINAIRE POWER 14.3W at 120V

RATED LIFE See LED bulb manufacturer specification

Delivered: 772 lm (LM-79) **LUMEN OUTPUT**

120V **INPUT VOLTAGE**

DRIVER OUTPUT No

CONSTRUCTION Plated Steel and Glass **DIFFUSER** - Perforated Metal


FINISHES Polished Chrome (-14), Satin Nickel (-24), Satin Copper

(-25), Aged Brass (-40)

MOUNTING 4" Octagonal J-Box with optional backplate, 2"x 3" J-Box

ETL Dry/Damp listed, ADA compliant, Conforms to UL STD **STANDARDS**

1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 4.00" H: 20.00" Ext: 3.50"

14.00" From top of fixture M.C:

With optional backplate W: 4.75"

20.00" H: 3.625" Ext:

M.C: 14.00" From top of fixture

Order example for standard fixture:

3-504-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v



