OOR TUNABLE WHITE 0-10V 96 WATT LED POWER SUPPLY

24VDC INDOOR CONSTANT VOLTAGE. TWO CHANNEL CONTROLS. FOR INTENSITY AND COLOR TEMPERATURE




REV 10.20.21

DESIGNED BY GREGORY KAY I ASSEMBLED IN AMERICA




PSB-96W-010-24VDC-2XK



0.05 (0.1cm)2.18" (1) (1) (5.5cm) (5.1cm) R

SIDE VIEW



PSB-96W-010-24VDC-2XK-TB (T-BAR GRID CEILING)

STANDARD & T-BAR DIMENSIONS		
	A	В
PSB-96W-010-24VDC-2XK	6.48"	12.15"
PSB-2X96W-010-24VDC-2XK	10"	14"
PSB-3X96W-010-24VDC-2XK	13"	17"
PSB-4X96W-010-24VDC-2XK	13"	17"

DESCRIPTION

Accepts input voltage in a range of 120 - 277VAC and outputs 24VDC power up to 96 watts. The low voltage output dims down to 1% when two additional wires are connected to a 0-10V dimmer. The enclosure provides a space inside for electrical connections. In-Wall Power Supply Kit includes power supply, box cover and stud hangers. T-Bar Mounting Kit includes power supply, box cover, and T-bar hangers for installing Junction Box above ceiling with in easy reach. Comes with 4' of 14 gauge pair Teflon cables with quick secure connectors. Power Supply features short circuit, overload and over temperature protection.

APPLICATIONS

Indoor, Damp Location

MOUNTING

Surface mounted with conduit access

POWER INPUT

120-277VAC

POWER OUTPUT

Class 2; 24 volts DC 4A, up to 96 watts maximum

EFFICIENCY

90%

AMBIENT OPERATING TEMPERATURE

-25° C to 40° C

DIMMING


#1 Controls the intensity. #2 Controls the Color Temperature. 0-10V (dimmer needs to be capable to dim to 0% without ON/OFF switch)

DIMMING CURVE

Linear, Logarithmic 100% - 0% (HydraDrive)

COMPLIANCE

Made in the USA, UL, CE, Title 24
*Title 24 with JA8 listed PureEdge products and systems



*96 watts only

Color

IN-WALL DIMENSIONS

В


14.25'

Α

8.5



PSB-96W-010-24VDC-2XK-IW



PSB-96W-010-24VDC-2XK-IW (IN WALL KIT)

	•	•	
_			

PSB-96W-010-24VDC-2XK-IW

PROJECT	FIXTURE TYPE	DATE	




INDOOR TUNABLE WHITE 0-10V 96 WATT LED POWER SUPPLY




24VDC INDOOR CONSTANT VOLTAGE, TWO CHANNEL CONTROLS, FOR INTENSITY AND COLOR TEMPERATURE


REV 10.20.21


Application: 0-10V dimming for Tunable White LED Strip/Fixture



T-BAR GRID CEILING







PSB-96W	-010-24VDC	-2XK-IW
---------	------------	---------

PROJECT	FIXTURE TYPE	DATE	