



S9870

2.5G16/LED/CL/27K/120V
 2.5 watt G16.5 LED; Clear; Candelabra base; 2700K; 200 lumens; 120 volts

Features

- Solid State LED lighting
- Long life
- Dimmable
- Approved for enclosed fixtures



S9870

Item Number	UPC	Voltage	Watts	Incandescent Equivalent	Lamp Shape	Base	ANSI Base
S9870	045923098703	120	2.5	25W	G16 1/2	Candelabra	E12

Lamp Code	Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
2.5G16/LED/CL/27K/120V	Dimmable	Compatible dimmers for S9870	Clear	3 3/16"	2-1/16"	200	15000

Kelvin Temp	Color	CRI	Package Type	RoHS Compliant	Fixture Type	UL or ETL Listed	UL Classification
2700	Warm White	80	Box	Yes	Enclosed Rated	Yes	cULus - Damp Location Rated

Warranty							
3 Year Limited							



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S9871

3.5G16.5/LED/CL/27K/120V
 3.5 watt G16.5 LED; Clear; Candelabra base; 2700K; 350 lumens; 120 volts

Features

- Solid State LED lighting
- Long life
- Dimmable
- Approved for enclosed fixtures



S9871

Item Number	UPC	Voltage	Watts	Incandescent Equivalent	Lamp Shape	Base	ANSI Base
S9871	045923098710	120	3.5	25W	G16 1/2	Candelabra	E12

Lamp Code	Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
3.5G16.5/LED/CL/27K/120V	Dimmable	Compatible dimmers for S9871	Clear	3 3/16"	2-1/16"	350	15000

Kelvin Temp	Color	CRI	Package Type	RoHS Compliant	Fixture Type	UL or ETL Listed	UL Classification
2700	Warm White	80	Box	Yes	Enclosed Rated	Yes	cULus - Damp Location Rated

Warranty
3 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

