

An architectural profile reminiscent of beautifully classic roof lines delivers significant light output in this modern LED wall sconce suitable for both indoor and outdoor applications. The Pitch Single's die-cast metal body houses powerful LED light sources that create visual appeal as light cascades down along a wall.

# High quality LM80-tested LEDs

for consistent long-life performance and color

# Outstanding protection against the elements:

- Marine-grade powder coat finishes
- · Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

# Can be mounted for up lighting or down lighting

#### **SPECIFICATIONS**

DELIVERED LUMENS	823
WATTS	26.1
VOLTAGE	120V, 277V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Downlight or Uplight
ССТ	3000K
CRI	80+
COLOR BINNING	3 Step
BUG RATING	B1-U0-G0
DARK SKY	Compliant (Downlight)
WET LISTED	IP65
GENERAL LISTING	ETL, Title 24
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years

 $<sup>\</sup>mbox{\ensuremath{^{\star}}}$  Visit techlighting.com for specific warranty limitations and details.



PITCH SINGLE shown in black



PITCH SINGLE shown in charcoal



PITCH SINGLE shown in bronze



PITCH SINGLE shown in silver

# ORDERING INFORMATION

700WSPIT	SIZE	FINISH	LAMP	
	<b>S</b> SINGLE	B BLACK Z BRONZE H CHARCOAL I SILVER		LED 80 CRI, 3000K 120V LED 80 CRI, 3000K 277V

# PITCH SINGLE WALL SCONCE








Pitch Single

# PHOTOMETRICS\*

\*For latest photometrics, please visit www. techlighting.com/OUTDOOR

#### PITCH SINGLE

Total Lumen Output: 823
Total Power: 26.2
Luminaire Efficacy: 31.4
Color Temp: 3000K
CRI: 80+
BUG Rating: B1-U0-G0



# PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

© 2016 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.

GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500



An architectural profile reminiscent of beautifully classic roof lines delivers significant light output in this modern LED wall sconce suitable for both indoor and outdoor applications. The Pitch Double's die-cast metal body houses powerful LED light sources that create visual appeal as light cascades from one angular tier to the next.

# High quality LM80-tested LEDs

for consistent long-life performance and color

# Outstanding protection against the elements:

- Marine-grade powder coat finishes
- · Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

# Can be mounted for up lighting or down lighting

#### **SPECIFICATIONS**

DELIVERED LUMENS	1193
WATTS	47.5
VOLTAGE	120V, 277V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Downlight or Uplight
ССТ	3000K
CRI	80+
COLOR BINNING	3 Step
BUG RATING	B1-U1-G0
DARK SKY	Compliant (Downlight)
WET LISTED	IP65
GENERAL LISTING	ETL, Title 24
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years

<sup>\*</sup> Visit techlighting.com for specific warranty limitations and details.



PITCH DOUBLE shown in black



PITCH DOUBLE shown in charcoal



PITCH DOUBLE shown in bronze




PITCH DOUBLE shown in silver

#### ORDERING INFORMATION

700WSPIT	SIZE	FINISH	LAMP	
	<b>D</b> DOUBLE	B BLACK Z BRONZE H CHARCOAL I SILVER		LED 80 CRI, 3000K 120V LED 80 CRI, 3000K 277V






Pitch Double

# PHOTOMETRICS\*

\*For latest photometrics, please visit www. techlighting.com/OUTDOOR

#### PITCH DOUBLE

Total Lumen Output: 1193
Total Power: 47.5
Luminaire Efficacy: 25.1
Color Temp: 3000K
CRI: 80+
BUG Rating: B1-U1-G0



# PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500





An architectural profile reminiscent of beautifully classic roof lines delivers significant light output in this modern LED wall sconce suitable for both indoor and outdoor applications. The Pitch Triple's die-cast metal body houses powerful LED light sources that create visual appeal as light cascades from one angular tier to the next.

# High quality LM80-tested LEDs

for consistent long-life performance and color

# Outstanding protection against the elements:

- Marine-grade powder coat finishes
- · Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

# Can be mounted for up lighting or down lighting

# **SPECIFICATIONS**

DELIVERED LUMENS	1486
WATTS	63.6
VOLTAGE	120V, 277V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Downlight or Uplight
ССТ	3000K
CRI	80+
COLOR BINNING	3 Step
BUG RATING	B1-U2-G1
DARK SKY	Compliant (Downlight)
WET LISTED	IP65
GENERAL LISTING	ETL, Title 24
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years

<sup>\*</sup> Visit techlighting.com for specific warranty limitations and details.



PITCH TRIPLE shown in black



PITCH TRIPLE shown in charcoal




PITCH TRIPLE shown in bronze



PITCH TRIPLE shown in silver

# ORDERING INFORMATION

700WSPIT	SIZE	FINISH	LAMP	
	T TRIPLE	B BLACK Z BRONZE H CHARCOAL I SILVER		LED 80 CRI, 3000K 120V LED 80 CRI, 3000K 277V




Pitch Triple

# PHOTOMETRICS\*

\*For latest photometrics, please visit www. techlighting.com/OUTDOOR

#### PITCH TRIPLE

Total Lumen Output: 1486
Total Power: 63.6
Luminaire Efficacy: 23.3
Color Temp: 3000K
CRI: 80+
BUG Rating: B1-U2-G1



# PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES



GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500