

LOW-VOLTAGE PENDANTS

Firefrost Pendant

DESCRIPTION

Murano glass with frosted or case glass interior. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAAA® module and six feet of field-cutttable suspension cable. Works with SORAA.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS


SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

2lb / 0.91kg ±



chartreuse



amber



chartreuse



cobalt



red



white

ORDERING INFORMATION

700 SYSTEM	FIRF	COLOR	FINISH	LAMP
FJ	FREEJACK	A	Z	12 VOLT HALOGEN
KL	KABLE LITE	H	C	-LEDS830 12 VOLT LED 80 CRI 3000K
MP	MONOPOINT	B	S	-24 24 VOLT HALOGEN
MO	MONORAIL	R		
MO2	TWO-CIRCUIT MONORAIL	W		

Note: Note: MP includes 4" Round Flush Canopy and is available in 120v only (for 277v order as FJ).

Antique Bronze is not available for Kable Lite.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ FIRF _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2016 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.