120/277VAC, 600MA (9-23VDC)

Dimmable Remote Power Supply





Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



 Model & Product
 L x W x H

 PS-0600A-UR1
 8 7%" X 2" X 1 ½"

PRODUCT DESCRIPTION

This class 2, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring low voltage fixtures. Class 2 power supply is intrinsically safer because It is considered safety from a fire initiation standpoint and provides acceptable protection from electric shock. Enclosure cover is easy to remove. Power supply has knockouts for line voltage wiring. Secondary wiring for class 2 power supply do not require conduit sheathed cable or clamp wiring techniques. May be dimmed using phase cut (TRIAC/ELV) or 0-10V dimmer.

FEATURES

- Universal Input 120-277VAC
- $\geq 0.9 \text{ pf}$
- · Overload and short circuit protection
- TRIAC/ ELV/0-10V Dimming Control
- 0-10V Dimming curve adjustment
- · Class 2 Output
- 5 Year warranty

SPECIFICATIONS

Input: 120-277VAC **Output:** 600mA, 9-23VDC

Dimming: TRIAC/ELV/0-10V: 100-1%

0-10V Minimum Current Source: 25uA 0-10V Maximum Current Sink: 400uA

Rated Life: 50,000 hours

Mounting: Can be mounted on ceiling or wall in all orientations

Standards: UL, cUL, Damp Location Listed,

Operating Temp: -4°F to 104°F (-20°C to 40°C)

LINE DRAWING



NOV 2022