

AETHER 2" - Round Adjustable Trim

R2ARAT

WAC®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

FEATURES

- Designed to fit in tight plenum
- 2" trim aperture, 2" housing height
- Damp Location Trims: 0-30° vertical and 365° horizontal adjustment
- Wet Location Trims: 0-25° vertical and 365° horizontal adjustment
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim with die-cast aluminum heat sink
Dimming: 100% - 5% with 0-10V
 100% - 5% with Electronic Low Voltage (ELV)/ TRIAC
Input: 120V-277V AC
Power: 9W, 15W, power factor 0.9
Mounting: Retention clips firmly hold trim to housing
Finish: Powder Coated White, Black/White, Haze/White, Black
Ceiling thickness: ½" - 1"
Standards: UL & cUL Damp Listed, UL & cUL Wet Listed (Lensed options only), Title 24 JA8 Compliant

Trim (See next page for housing)	Model	Beam	Color Temp	CRI	Lumens*	CBCP*	Finishes
	R2ARAT Round, 0-30° Adjustable Damp Location	S 15°	827 2700K 85 835 8045	BK Black BKWT Black/White HZWT Haze/White WT White			
			830 3000K 85 885 8535				
			835 3500K 85 905 8740				
			840 4000K 85 915 8810				
			927 2700K 90 690 6625				
		930 3000K 90 720 6935					
		N 26°	827 2700K 85 1270 4270	BK Black BKWT Black/White HZWT Haze/White WT White			
			830 3000K 85 1345 4525				
			835 3500K 85 1375 4635				
	840 4000K 85 1390 4675						
	F 40°	927 2700K 90 1050 3535	BK Black BKWT Black/White HZWT Haze/White WT White				
		930 3000K 90 1095 3680					
827 2700K 85 1260 2515							
R2ARAT Round, 0-25° Adjustable Lensed, Wet Location	S 16°	830 3000K 85 1335 2670	LBK Lensed Black LBKWT Lensed Black/White LHZWT Lensed Haze/White LWT Lensed White				
		835 3500K 85 1370 2735					
		840 4000K 85 1380 2755					
		927 2700K 90 1045 2085					
		930 3000K 90 1090 2170					
	N 28°	827 2700K 85 1160 2220	LBK Lensed Black LBKWT Lensed Black/White LHZWT Lensed Haze/White LWT Lensed White				
		830 3000K 85 1245 3905					
		835 3500K 85 1275 4000					
		840 4000K 85 1285 4030					
	F 40°	927 2700K 90 970 3050	LBK Lensed Black LBKWT Lensed Black/White LHZWT Lensed Haze/White LWT Lensed White				
		930 3000K 90 1015 3175					
		827 2700K 85 1160 2220					
			830 3000K 85 1230 2355	LBK Lensed Black LBKWT Lensed Black/White LHZWT Lensed Haze/White LWT Lensed White			
		835 3500K 85 1260 2415					
		840 4000K 85 1270 2430					
		927 2700K 90 960 1840					
		930 3000K 90 1000 1915					

R2ARAT- _____ - _____

Please see next page for housing (required)

Example: **R2ARAT-N930-WT**

wacighting.com	Headquarters, East Manufacturing Facility	South East Manufacturing Facility	Central Manufacturing Facility	West Manufacturing Facility
Phone (800) 526.2588	44 Harbor Park Drive	1600 Distribution Ct	1700 South J Elmer Freeway, Ste 100	1750 S Archibald Ave
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

AETHER 2" - Round Adjustable Trim Housing



*Lumen and CBCP data are shown for 15W (HR-2LED-H13A, HR-2LED-H13AC, HR-2LED-R15A) housings. Use 0.66 multiplier to determine data for 9W (HR-2LED-R10A) housing.

Example: R2ARAT-F840-LWT with 9W housing: 1270 lm x 0.66 = 838 lm

2430 CBCP x 0.66 = 1604 CBCP

Housing	Model
	HR-2LED-H13A New Construction (15W) IC-rated, Airtight
	HR-2LED-H13AC New Construction (15W) IC-rated, Airtight Chicago Plenum
	HR-2LED-R10A Remodel (9W) IC Rated, Airtight
	HR-2LED-R15A Remodel (15W) Non-IC Rated, Airtight

HR-2LED-_____

Example: **HR-2LED-H13A**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761