


HR2LD-ET109P

2" Tesla™ Pro LED High Brightness Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round, High Brightness downlight trim with glass lens

FEATURES

- 2" aperture
- High Brightness Trim
- Energy Star® rated
- CEC Title 24 Compliant (see below for list of models)
- Wet location listed
- 9° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+


Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® and 2013 California Title 24 qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	2013 Title 24	Finish
HR2LD-ET109P <i>High Brightness Wet Location Listed</i>	N 30°	827 2700K	85	955	1765	Yes	No	BN Brushed Nickel CB Copper Bronze WT White 
		927 2700K	90	775	1436	Yes	Yes	
		830 3000K	85	990	1807	Yes	No	
		930 3000K	90	880	1619	Yes	Yes	
		835 3500K	85	1080	2015	Yes	No	
		840 4000K	85	1090	2035	Yes	No	
	F 55°	827 2700K	85	935	972	Yes	No	
		927 2700K	90	760	777	Yes	Yes	
		830 3000K	85	975	995	Yes	No	
		930 3000K	90	860	878	Yes	Yes	
		835 3500K	85	1055	1090	Yes	No	
		840 4000K	85	1075	1106	Yes	No	

HR2LD-ET109P

Example: HR2LD-ET109PF835CB

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

REPLACEMENT MODULES

Model	Input	Notes
HR-2LED-H09D-ICA	120V -277V	Ceiling thickness: ½"–¾"
HR-2LED-H09D-ICAC		
HR-2LED-R09D-A	120V -277V	Requires 3" of clearance from insulation on all sides Ceiling thickness: ½"–1"

Reflectors	
Narrow Flood	SL-REF-BL10-1-N
Flood	SL-REF-BL10-1-F

LED		
2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760