


HR3LD-ET118P

3.5" Tesla™ Pro LED High Brightness Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round, High Brightness downlight trim with glass lens

FEATURES

- 3.5" aperture
- High Brightness Trim
- Energy Star® rated
- Wet location listed
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Power Consumption: 21.5W

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing.

Finish: Powder coated white
Electroplated brushed nickel and copper bronze

Standards: ETL & cETL Listed. See table below for Energy Star® qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LD-ET118PF High Brightness Wet Location Listed	48°	827 2700K	85	1290	1632	Yes	BN Brushed Nickel CB Copper Bronze WT White
		927 2700K	90	1065	1339	Yes	
		830 3000K	85	1290	1607	Yes	
		930 3000K	90	1185	1504	Yes	
		835 3500K	85	1445	1812	Yes	
		840 4000K	85	1460	1827	Yes	

HR3LD-ET118PF

Example: **HR3LD-ET118PF835CB**

COMPATIBLE HOUSINGS *See individual housing spec sheets for complete information.*

New Construction

HR-3LED-H18D1-ICA Narrow, IC-Rated, Airtight	120V-277V	HR-3LED-H18D1-ICAC Narrow, IC-Rated, Airtight Chicago Plenum	120V-277V
HR-3LED-H18D-ICA IC-Rated, Airtight	120V-277V	HR-3LED-H18D-ICAC IC-Rated, Airtight Chicago Plenum	120V-277V
HR-3LED-H18D-EMICA IC-Rated, Airtight Emergency Backup Battery	120V	HR3LED-H18D-EMICAF IC-Rated, Airtight Emergency Backup Battery	277V
HR-3LED-H18D-A New Construction Non-IC, Airtight	120V-277V		

Remodel

HR-3LED-R18D-A Non-IC, Airtight	120V-277V	HR-3LED-R22D Non-IC	120V-277V
---	-----------	-------------------------------	-----------

REPLACEMENT MODULES

Reflectors

Narrow Flood Flood	SL-REF-BL10-1-N SL-REF-BL10-1-F
-----------------------	--

LED

2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760