


HR3LEDT218P

3.5" Tesla™ Pro LED Shower Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round shower trim with interior open reflector.

FEATURES

- 3.5" aperture
- Energy Star® rated
- Wet location listed
- 30° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Power Consumption: 21.5W


Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing.

Finish: Powder coated white
Electroplated brushed nickel and copper bronze

Standards: ETL & cETL Listed. See table below for Energy Star® qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LEDT218PN <i>Shower Light</i> <i>Wet Location Listed</i>	30°	827 2700K	85	1100	2274	Yes	BN <i>Brushed Nickel</i> CB <i>Copper Bronze</i> WT <i>White</i> 
		927 2700K	90	920	1896	Yes	
		830 3000K	85	1135	2316	Yes	
		930 3000K	90	1040	2153	Yes	
		835 3500K	85	1240	2569	Yes	
840 4000K	85	1256	2547	Yes			

HR3LEDT218PN

Example: HR3LEDT218PN927BN

COMPATIBLE HOUSINGS *See individual housing spec sheets for complete information.*

New Construction

HR-3LED-H18D1-ICA <i>Narrow, IC-Rated, Airtight</i>	120V-277V	HR-3LED-H18D1-ICAC <i>Narrow, IC-Rated, Airtight Chicago Plenum</i>	120V-277V
HR-3LED-H18D-ICA <i>IC-Rated, Airtight</i>	120V-277V	HR-3LED-H18D-ICAC <i>IC-Rated, Airtight Chicago Plenum</i>	120V-277V
HR-3LED-H18D-EMICA <i>IC-Rated, Airtight Emergency Backup Battery</i>	120V	HR3LED-H18D-EMICAF <i>IC-Rated, Airtight Emergency Backup Battery</i>	277V
HR-3LED-H18D-A <i>New Construction Non-IC, Airtight</i>	120V-277V		

Remodel

HR-3LED-R18D-A <i>Non-IC, Airtight</i>	120V-277V	HR-3LED-R22D <i>Non-IC</i>	120V-277V
--	-----------	--------------------------------------	-----------

REPLACEMENT MODULES

Reflectors

<i>Narrow Flood Flood</i>	SL-REF-BL10-1-N SL-REF-BL10-1-F
---------------------------	--

LED

2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760