### **R4FSWT**

## 4" FQ - Square Wall Wash Trim





### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### **FEATURES**

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

Fixture Type:
Catalog Number:
Project:
Location:

#### **SPECIFICATIONS**

Construction:Durable die-cast aluminum constructionInputUniversal 120-277V AC 50/60 HzDimming:Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

**Standards:** ETL & cETL Wet Location Listed,

Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
			1770	N/A	<b>927</b> 2700K	90		
5%"	<b>R4FSWT</b> Square Trim	A Asym	1865	N/A	<b>930</b> <i>3000K</i>	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
⊢ 3" → ├── 5¼" ──			1900	N/A	<b>935</b> 3500K	90		

R4FSWT-\_\_-

Example: R4FSWT-930-WT

\*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multip	liou	TF		
Multiplier		927	930	935
	4	0.95	1.00	1.02
HOUSING	3	0.84	0.88	0.90
noosiita	2	0.65	0.68	0.70
	1	0.45	0.47	0.48

Example: R4FSWT-930-WT with 1 housing: 1865 lm (Reference Output) x 0.47 (Multiplier) = 875 lm

Please see next page for housing units (required)

waclighting.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (800) 526.258844 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91761

## **R4FSWT**

# 4" FQ - Square Wall Wash Trim



HOUSING (Required)		Model	Trim	Power	Emergency Backup
New Construction IC Airtight	10"  14%"  14%"  14%"  14%"  17%"	R4FBNT		1 13W IC 2 19W IC 3 25W IC 4 28W Non-IC	<b>EM</b> Optional
New Construction Frame-in Non-IC	10" L4%" - 24"max  14%" - 17%"	R4FBFT		1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	<b>EM</b> Optional
Remodel Non-IC	2½" 5½" 5½"  2"  2"	R4FBRT		1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	N/A

R4FB\_\_\_-

Example: R4FBNT-3 or R4FBNT-3-EM (with Emergency backup battery)

### R4FSWT-WD

### 4" FQ - Square Wall Wash Trim (Dim-To-Warm)





Catalog Number:	
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

### **FEATURES**

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

Fixture Type:

**Construction:** Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
55%"	<b>R4FSWT</b> Square Trim	A Asym	950	N/A	<b>WD</b> 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

### R4FSWT-WD-\_

Example: R4FSWT-WD-WT

\*Lumens shown in the table is a reference value for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier		TRIM
HOUSING	2	1.00
	1	0.69

Example: R4FSWT-WD-WT with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Please see next page for housing units (required)

waclighting.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (800) 526.258844 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91761

## **R4FSWT-WD**

# WAC

# 4" FQ - Square Wall Wash Trim (Dim-To-Warm)

HOUSING (Required)		Model	Power	Emergency Backup
New Construction IC Airtight	10"  1434"  1736"	R4FBNT	1 13WIC 2 19WIC	<b>EM</b> Optional
New Construction Frame-in Non-IC	10" - 45%" - 24"max - 1434" - 173%"	R4FBFT	1 13W Non-IC 2 19W Non-IC	<b>EM</b> Optional
Remodel Non-IC	2½"  -5½"  2½"	R4FBRT	1 13W Non-IC 2 19W Non-IC	N/A

R4FB\_\_-

Example: R4FBNT-2 or R4FBNT-2-EM (with Emergency backup battery)