LOW VOLTAGE - model ME-826


_

WAC LIGHTING

Responsible Lighting®

LED MR16 Display Spot Light





Fixture Type:	
Catalog Number:	
Project:	
Location:	

LED

Power: 8W/ 3000K Color Temp: Lumens: 450 CRI: 85 CBCP: 833 Dimming: Yes Comparable: 35 W MR16 Rated Life: 25,000 hours

PRODUCT DESCRIPTION

Engineered with an integral transformer and designed for mounting to walls or ceilings, Display Spot Lights deploy optimal accent lighting from surface mounted canopies that can be custom designed with any of WAC low voltage track heads.

FEATURES

- · Integral Electronic transformer
- Accepts 12V LED MR16, Halogen MR16 lamps up to 50W max
- · LED MR16 included when ordered as LED
- · 1 watt minimum load
- Can be wall or ceiling mounted
- Available extensions from 6 to 48 inches
- Fixtures available with 6", 12", 18", 24", 36", 48", 72" and 96" extensions (factory assembled in BK, WT, or BN). Specify fixture style and finish when ordering (i.e.: ME-826LED-X6-BK). Extended fixtures are available only as a complete unit from the factory.
- Special lens types such as spread lenses and UV lenses can be ordered from WAC and used in place of the supplied clear lens.

SPECIFICATIONS

Construction: Die-cast aluminum fixture with bi-pin ceramic socket and 18 gauge teflon insulated wires, with fiberglass sleeves. Supplied with tempered clear glass lens.

Transformer: 120V/12V Electronic transformer with auto reset, soft start, and short circuit protection features.


Dimming: Smooth and continuous ELV dimming to 10%

Aiming: 350° horizontal rotation and 90° vertical aiming. Two aiming screws (one on each side of fixture) allow for locking fixture aiming angle.

Standards: UL & CUL Listed

ORDER NUMBER

Model #	Lamping	Extension (Optional)		Finish	
ME-826LED ME-826	LED Halogen	X6 X12 X18 X24 X36 X48	6" 12" 18" 24" 36" 48"	BK BN WT	Black Brushed Nickel White



Example: ME-826LED-BK or ME-826LED-X6-BK

ALTERNATIVE LEN	Color	Color		
Color Lens	LENS-16	AMB BLU GRN RED YEL	Amber Blue Green Red Yellow	
UV Filter Lens Frosted Lens Spread Lens Beam Elongating Honeycomb Louver	LENS-16-UVF LENS-16-FR LENS-16-SPR LENS-16-BEL LENS-16-HCL			

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585