

lightology.com 866-954-4489 12-07-25

Project:			
Company:			
Location:	Fixture Type:		
SPEC #: LPL1011019			
Approved On:	Approved By:		

Flindt 24V Outdoor Bollard By Louis Poulsen











Description


The Flindt 24V Outdoor Bollard emits a wide, downward directed, glare-free light. The light source rests at the top inside the asymmetric carving on the side of the bollard, where the gradient serves as a reflector that softens the light and forms a pleasant organic shape on the ground below. A horizontal connection line underline the two parts of the bollard. Mounting options include: Spike Mount for use in soil or gravel. Spike mount bollards come pre-wired with a weatherproof 12 inch connector cable for aboveground use. Anchor Mounts are designed for use in new concrete pads and require professional belowground cabling. Baseplate Mounts include a baseplate for securing the bollard to existing concrete or decks and are designed for use with professional below-ground cabling. Anchor and Baseplate fixtures include inputs for professional cabling.Note:Required power supply sold separately. T-connector included with Spike mount options. Optional extension cable available for Spike mount options.

Specifications

COLOR
BODY FINISH Natural Aluminum
WATTAGE
DIMMER Not Dimmable
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
COLOR RENDERING
LAMP COLOR
LUMENS/WATT



Shown in natural aluminum





CLICK TO VIEW PRODUCT

Notes:				
--------	--	--	--	--