

lightology.com 866-954-4489 07-04-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>RAD1011286</b>	
Approved On:	Approved By:

## Tamper Resistant GFCI Outlet By Legrand Radiant



## Description

Radiant Spec Grade 15 or 20 Amp Tamper Resistant Self Test GFCI conducts an automatic test every three seconds, ensuring it's always ready to protect. If the device fails the test, the indicator light flashes to signal that the GFCI should be replaced. It also has our proven SafeLock Protection feature: if critical components are damaged and protection is lost, power to the receptacle is disconnected. Feedthru wiring configuration allows GFCI to protect downstream receptacles. Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly. Feed-thru wiring configuration allows GFCI to protect downstream receptacles. High-impactresistant thermoplastic construction. Class A rated GFCI. UL Standard. UL listed.Note: >/B> Radiant Screwless Wall Plate sold separately.



Shown in graphite



Dimensions for 15 & 20 Amp

## Specifications

COLOR	•	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠				IN/	А
BODY FINISH .																												Gr	ар	hit	e
WATTAGE																														N/	Ά
DIMMER																														N/	Ά
DIMENSIONS .																					1.	73	"V	V:	χ 4	4.2	"H	łχ	1.0	3"	D
BULB																														N/	Ά



**CLICK TO VIEW PRODUCT** 

Notes:

NI/A