

Lightology

lightology.com
866-954-4489
04-22-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG1023518**
 Approved On: _____ Approved By: _____

Flex Neon LRF5 Indoor/Outdoor Static White Left/Right Bend By PureEdge Lighting



Description

The Flex Neon LRF5 with a 0.5 inch wide flat lens bends left or right and features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads). May be surface or flush mounted. Choose from two wattage and a variety of color temperature options including Warm Dim 27D (2700K-2000K). Sold in 5 foot increments up to 20 feet (5 watt). Universal power supply dimmable with an electronic low voltage (ELV), Triac, or 0-10V dimmer, sold separately. ETL listed. 5-year pro-rated warranty. IP65 rated for outdoor wet locations. Product is built to order. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). System requires Outdoor Rated Power Supply and Outdoor Power Supply Enclosure. Optional mounting accessories sold separately.

Specifications



COLOR	White
BODY FINISH	N/A
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	60"L x 0.56"W x 0.7"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
BEAM ANGLE	120°
COLOR RENDERING	92 CRI
LAMP COLOR	2700K
LUMENS/WATT	212.00
LUMINOUS FLUX	1060 lumens



Shown in white



Bends Right to Left or Left to Right



CLICK TO VIEW PRODUCT

Notes: