

lightology.com 866-954-4489 11-05-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1023518	
Approved On:	Approved By:

Flex Neon LRF5 Indoor/Outdoor Static White Left/Right Bend By PureEdge Lighting









Description

The Flex Neon LRF5 with a 0.5 inch wide flat lens bends left or right and features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads). May be surface or flush mounted. Choose from two wattage and a variety of color temperature options including Warm Dim 27D (2700K-2000K). Sold in 5 foot increments up to 20 feet (5 watt). Universal power supply dimmable with an electronic low voltage (ELV), Triac, or 0-10V dimmer, sold separately. ETL listed. 5-year pro-rated warranty. IP65 rated for outdoor wet locations. Product is built to order. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). System requires Outdoor Rated Power Supply and Outdoor Power Supply Enclosure.Optional mounting accessories sold separately.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 5 y LED/5W/24V LED

Technical Information

LAMP LIFE .														50000 hours
BEAM ANGLE														120°
COLOR RENDE	RING													92 CRI
LAMP COLOR														2700K
LUMENS/WATT	٠													212.00
LUMINOUS FLU	JX .													. 1060 lumens



Shown in white







CLICK TO VIEW PRODUCT

Notes: