

# Lightology

lightology.com  
866-954-4489  
05-09-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG1028047**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## MIYO Pix Sticks Tie Stix Suspension

By PureEdge Lighting



### Description

MIYO Make-It-Your-Own Pix Sticks Tie Stix Suspension system allows you to become the lighting designer. Mix & match your channel lengths or keep them all the same in configurations of 2, 3, 4, 5, 6, 7 or 9-light options. Available in increments from 39 to 96 inch, 5 or 7 watts per foot, and multiple wood and metal channel finish options. Offered in a variety of color temperature options including two Warm Dim options of 2700K (27D) or 3000K (30D) that dim down to 2000K. Includes two 12 foot adjustable aircraft cables per channel length. Requires a canopy and Universal (UNI), electronic low voltage (ELV), 0-10V or Lutron Hi-Lume power supply. 5 year pro-rated warranty. ETL listed. Suitable for damp locations. Title 24 compliant when used with Universal (UNI) power supply. Product is built to order. NOTE: A 24VDC REMOTE POWER SUPPLY AND MULTI-LIGHT CANOPY ARE REQUIRED AND SOLD SEPARATELY. Canopy and Hardware Finishes: Satin Black, Antique Bronze, Chrome, Satin Nickel and White. Channel Finishes: Satin Black, Chrome (available up to 84 inch length), Satin Nickel, White, Satin Brass, Maple, Walnut, Cherry, White Oak and Wood Espresso.

### Specifications


COLOR . . . . . Wood Cherry  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 15W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 39"L x 1.24"W x 1.24"H  
INTEGRATED LED MODULE . . . . . 3 x LED/5W/24V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
BEAM ANGLE . . . . . 100°  
COLOR RENDERING . . . . . 95 CRI  
LAMP COLOR . . . . . 2700K  
LUMENS/WATT . . . . . 178.80  
LUMINOUS FLUX . . . . . 894 lumens



Shown in satin nickel / wood cherry



CLICK TO VIEW PRODUCT

Notes: