

Lightology

lightology.com
866-954-4489
08-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG1034628**
Approved On: _____ Approved By: _____

Cirrus Ceiling 1R Canopy Wall Grazer w/ Remote Power

By PureEdge Lighting



Description

Cirrus Ceiling Channel Wall Grazer with Remote Power and rectangle 1 inch canopy is a linear LED fixture that brings to life undulating and textured surfaces. May be recessed in ceiling, perimeter or cove. Available in a 5 or 7 watt option in various increments from 12 to 120 inches, features a clear lens with a 10 degree or frosted lens with a 20 degree beam spread, a variety of finish options, and a spectrum of color temperatures including Warm Dim and Tunable White. Chrome finish available up to 84 inch length. Channel includes a 1 inch rectangle canopy with junction box. Ceiling lock clips (CC-MCL-L) are provided for support every 48 inches. Optional 1 inch canopy with junction box and 50 watt power supply sold separately. Title 24 compliant when used with a Universal (UNI) power supply. Product is built to order. Note: Requires a 24VDC remote Universal (UNI) power supply (universal dimming TRIAC, ELV, 0-10V), or a PS-60L 60 watt electronic low voltage (ELV) power supply (dimmable with an ELV dimmer) that fits within the junction box. Power supply, dimmer, and optional accessories sold separately.

Specifications


COLOR Clear
BODY FINISH White
WATTAGE 21W
DIMMER Low Voltage Electronic
DIMENSIONS 36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE 3 x LED/7W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 206.14
LUMINOUS FLUX 1443 lumens



Shown in white / clear



CLICK TO VIEW PRODUCT

Notes: