

Lightology

lightology.com
866-954-4489
03-12-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG1081266**
 Approved On: _____ Approved By: _____

Cirrus Ceiling Wall Wash with Glare Shield / Remote Power

By PureEdge Lighting



Description

The Cirrus Wall Wash with Glare Shield is designed to block glare and illuminate vertical surfaces from the top of the ceiling to the floor at a 3.3:1 ratio. Available with 5 watts per foot in one foot increments up to 96 nominal inches (lengths shown are actual). Features a standard diffused white wall wash lens and optional black or white louvers. Offered with a 4 inch square split canopy (4S) that mounts to a standard junction box or a Slim Profile Channel Junction Box (1R) with no visible canopy. Includes 4 inch square or 1 inch rectangle canopy, 6 foot whip, and mounting clips. Note: Requires a 24VDC remote Universal (UNI) power supply (universal dimming TRIAC, ELV, 0-10V) that can be located up to 40 feet away, or a PS-60L 60 watt electronic low voltage (ELV) power supply (dimmmable with an ELV dimmer) that fits within the junction box. Note: Required power supply, dimmer control, and optional accessories sold separately.

Specifications


COLOR	No Louver
BODY FINISH	Satin Nickel
WATTAGE	5W
DIMMER	Low Voltage Electronic
DIMENSIONS	13"L x 0.9"W x 1.25"H
INTEGRATED LED MODULE	1 x LED/5W/120V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	69.00
LUMINOUS FLUX	345 lumens



Shown in satin nickel / no louver



CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND BLACK LOUVER



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND LOUVER



CLICK TO VIEW PRODUCT

Notes: