

# Lightology

lightology.com  
866-954-4489  
08-04-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG1081266**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Cirrus Ceiling Wall Wash with Glare Shield / Remote Power

By PureEdge Lighting



### Description

The Cirrus Wall Wash with Glare Shield is designed to block glare and illuminate vertical surfaces from the top of the ceiling to the floor at a 3.3:1 ratio. Available with 5 watts per foot in one foot increments up to 96 nominal inches (lengths shown are actual). Features a standard diffused white wall wash lens and optional black or white louvers. Offered with a 4 inch square split canopy (4S) that mounts to a standard junction box or a Slim Profile Channel Junction Box (1R) with no visible canopy. Includes 4 inch square or 1 inch rectangle canopy, 6 foot whip, and mounting clips. Note: Requires a 24VDC remote Universal (UNI) power supply (universal dimming TRIAC, ELV, 0-10V) that can be located up to 40 feet away, or a PS-60L 60 watt electronic low voltage (ELV) power supply (dimmable with an ELV dimmer) that fits within the junction box. Note: Required power supply, dimmer control, and optional accessories sold separately.

### Specifications


COLOR . . . . . No Louver  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 5W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 13"L x 0.9"W x 1.25"H  
INTEGRATED LED MODULE . . . . . 1 x LED/5W/120V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 95 CRI  
LAMP COLOR . . . . . 2700K  
LUMENS/WATT . . . . . 69.00  
LUMINOUS FLUX . . . . . 345 lumens



Shown in satin nickel / no louver



CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND BLACK LOUVER



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND LOUVER



CLICK TO VIEW PRODUCT

Notes: