

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1081924	
Approved On:	Approved By:

Cirrus Ceiling Wall Wash Tunable White w/ Glare Shield By PureEdge Lighting





Description

The Cirrus 2K6K Tunable White Wall Wash with Glare Shield (remote power) is designed to block glare and illuminate vertical surfaces from the top of the ceiling to the floor at a 3.3:1 ratio. Available with 5 watts per foot in one foot increments up to 96 nominal inches (lengths shown are actual). Using the latest in LED technology Tunable White 2K6K (2000K-6500K) grants independent control and adjustment of color temperature and intensity from 2000K (sunset) through 6500K (daylight white). Features a standard diffused white wall wash lens and optional black or white louvers. Offered with choice of 4 inch square split canopy (4S) that mounts to a standard junction box or a Slim Profile canopy with junction box (1R) with no visible canopy, a 6 foot whip, and drywall Imounting clips (CC-MCL) every 18 inches. Optional accessories sold separately. Note: Requires a Tunable White 2XK power supply (with the CDMX-2XK Tunable White controller), or 0-10V 2-Channel Tunable White power supply (with two dimmers: one for intensity and one for color temperature), sold separately.


Specifications COLOR

BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
LAMP LIFE

LAMP LIFE
COLOR RENDERING
LAMP COLOR 2000K-6000K Tunable White
LUMENS/WATT
LUMINOUS FLUX 582 jumens



Shown in satin nickel / no louver





CLICK TO VIEW PRODUCT

Notes:	