

Lightology

lightology.com
866-954-4489
04-22-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG1093460**
 Approved On: _____ Approved By: _____

Flex Neon UDF7 Indoor/Outdoor Tunable White Up/Down Bend 24V

By PureEdge Lighting



Description

The Flex Neon Outdoor UDF7 Tunable White with a 0.7 inch wide flat lens bends up or down and features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads). May be surface or flush mounted. Sold in 5 foot increments up to 20 feet (5 watt). Dynamic Tunable White (2K6K) color temperature ranges from 2000K through 6500K (daylight). Tunable White allows for independent control for adjusting LED color temperature and brightness. ETL listed. 5-year pro-rated warranty. IP65 rated for outdoor wet locations. Product is built to order. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). System requires outdoor rated 24VDC Tunable White power supply with outdoor power supply enclosure, or 0-10V 2-channel Tunable White power supply, sold separately. Optional mounting accessories and dimmer control sold separately. Dimmable with 0-10V: Requires two dimmers, one for intensity and one for color temperature, or one DMX Dynamic Color Changing CDMX1 or CTP controller.

Specifications


COLOR	White
BODY FINISH	N/A
WATTAGE	25W
DIMMER	N/A
DIMENSIONS	60"L x 0.7"W x 0.5"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
BEAM ANGLE	120°
COLOR RENDERING	90 CRI
LAMP COLOR	2000K-6000K Tunable White
LUMENS/WATT	425.00
LUMINOUS FLUX	2125 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: