

lightology.com 866-954-4489 12-07-25

Project:	
Company:	
company.	
Location:	Fixture Type:
SPEC #: EDG1093464	
Approved On:	Approved By:

Flex Neon LRT7 Indoor/Outdoor Tunable White 3-Sided Lens By PureEdge Lighting







Description

LRT7 Flexible Neon Bends Left to Right with a 0.7 inch wide three-sided lens, offering superior color quality and performance while creating uniform illumination without visible dots. Flex Neon can be flush or surface mounted. Sold in 5 foot increments at 5 watts (4.4 watts) per foot up to 20 feet. Dynamic Tunable White (2K6K) color temperature option ranges from 2000K through 6500K (daylight). Tunable White allows for independent control for adjusting LED color temperature and brightness. IP65 rated for outdoor wet locations. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). Optional mounting accessories and dimmer control sold separately. System requires an outdoor rated 24VDC Tunable White power supply with outdoor power supply enclosure, or 0-10V 2-channel Tunable White power supply, sold separately. 0-10V Dimming: Requires two dimmers, one for intensity and one for color temperature. DMX Dynamic Color Changing: Requires CDMX1 controller. Note: Product is built to order

Specifications


COLOR																									W	hite
BODY FINISH																										N/A
WATTAGE																									. 2	25W
DIMMER																										N/A
DIMENSIONS																	6	50	"L	Х	0.7	7"۱	N	х	0.7	'5"H
INTEGRATED	ΙF	D	М	ı	ח	U	ΙF	-										5 ,	v I	FI	n/	5V	۸//	2	2/ [FD

Technical Information

LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
I UMINOUS FI UX



Shown in white







CLICK TO VIEW PRODUCT

Notes: