

lightology.com 866-954-4489 08-03-25

| Project: | Project: | | | | | | | | | | | | | |
|---------------------------|---------------|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Company: | | | | | | | | | | | | | | |
| Location: | Fixture Type: | | | | | | | | | | | | | |
| SPEC #: EDG1093468 | | | | | | | | | | | | | | |
| Approved On: | Approved By: | | | | | | | | | | | | | |

Saber Tunable White 0.8 Inch Round Outdoor Suspension By PureEdge Lighting







Description

The Saber Outdoor SCS8 Tunable White Suspension with a 0.8 inch wide round lens bends up and down and features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads). The Saber line is tension hung and bends up and down giving it the ability to traverse wall to wall, wall to ceiling, or floor to ceiling. 5 Watt sold in 5 foot increments up to 20 feet with power feed at one end with Dynamic Tunable White (27K6 or 2K6K) color temperature. 276K ranges from 2700K (incandescent-mimic) through 6500K (daylight). 2K6K ranges from 2000K through 6500K (daylight). Tunable White allows for independent control for adjusting LED color temperature and brightness. ETL listed. 5year pro-rated warranty. IP65 rated for outdoor wet locations. Product is built to order. System includes Outdoor 24VDC LED Flex Neon Saber, a Pair of Turnbuckles, 6 Feet Aircraft Cable, Power Connector (connected to each end of fixture), and Wet Location Barrel Connectors. System requires Outdoor Rated Power Supply or a 2XK 0-10V power supply, sold separately. Optional mounting accessories and dimmer control sold separately.2XK 0-10V power supply requires two dimmers, one for intensity and one for color temperature. DMX Dynamic Color Changing requires CDMX1 controller.

Specifications

| COLOR | | | | | | | | | | | | | | | | | | | | | | | | Wh | ite |
|--------------|----|-----|----|----|-------|-----|---|--|--|--|--|--|--|--|--|---|----|----|---|-----|-----|----|------------|-------|-----|
| BODY FINISH | | | | | | | | | | | | | | | | | | | | | | | | . N | I/A |
| WATTAGE | | | | | | | | | | | | | | | | | | | | | | | | . 25 | W |
| DIMMER | | | | | | | | | | | | | | | | | | | | | | | | . N | I/A |
| DIMENSIONS | | | | | | | | | | | | | | | | 6 | 50 | "L | Х | 0." | 75' | "V | V > | (1.12 | "H |
| INTEGRATED I | FD | ۸ (| 10 | חר |) L J | l F | = | | | | | | | | | | 5 | νI | F | n/ | 5V | \/ | 24 | | - D |

Technical Information

| LAMP LIFE |
|-----------------|
| BEAM ANGLE |
| COLOR RENDERING |
| LAMP COLOR |
| LUMENS/WATT |
| LUMINOUS FLUX |



Shown in white







CLICK TO VIEW PRODUCT

| Notes: | : | | | |
|--------|---|--|--|--|
|--------|---|--|--|--|