Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1093472**

Approved On: Approved By:

Flex Neon LRF5 Outdoor Tunable White Left / Right Bend


By PureEdge Lighting


Description

The LRF5 Flexible Neon features left or right bend with a 0.5 inch wide flat lens offering superior color rendering while creating uniform illumination without visible dots. May be surface or flush mounted. Sold in 5 foot increments at 5 watts (4.4 watts) per foot up to 20 feet. Dynamic Tunable White (2K6K) color temperature option. The 2K6K option ranges from 2000K through 6500K (daylight). Tunable White allows for independent control for adjusting LED color temperature and brightness. IP65 rated for outdoor wet locations. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). Optional mounting accessories and dimmer control sold separately. System requires outdoor rated Tunable White power supply with power supply enclosure, or 0-10V Tunable White 2-channel power supply, sold separately. Dimmable with 0-10V: Requires two dimmers, one for intensity and one for color temperature, or one DMX Dynamic Color Changing CDMX1-1. Note: Product is built to order.



Shown in white





Specifications

COLOR	White
BODY FINISH	N/A
WATTAGE	25W
DIMMER	N/A
DIMENSIONS	60"L x 0.56"W x 0.7"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
BEAM ANGLE	120°
COLOR RENDERING	90 CRI
LAMP COLOR	2000K-6000K Tunable White
LUMENS/WATT	246.20
LUMINOUS FLUX	1231 lumens

CLICK TO VIEW PRODUCT

Notes: