

Lightology

lightology.com
866-954-4489
07-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG1093473**
Approved On: _____ Approved By: _____

Flex Neon LRF5 Indoor/Outdoor Tunable White Left/Right Bend

By PureEdge Lighting



Description

The LRF5 Flexible Neon features left or right bend with a 0.5 inch wide flat lens offering superior color rendering while creating uniform illumination without visible dots. May be surface or flush mounted. Sold in 5 foot increments at 5 watts (4.4 watts) per foot up to 20 feet. Dynamic Tunable White (2K6K) color temperature option. The 2K6K option ranges from 2000K through 6500K (daylight). Tunable White allows for independent control for adjusting LED color temperature and brightness. IP65 rated for outdoor wet locations. System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). Optional mounting accessories and dimmer control sold separately. System requires outdoor rated Tunable White power supply with power supply enclosure, or 0-10V Tunable White 2-channel power supply, sold separately. Dimmable with 0-10V: Requires two dimmers, one for intensity and one for color temperature, or one DMX Dynamic Color Changing CDMX1-1. Note: Product is built to order.

Specifications



COLOR	White
BODY FINISH	N/A
WATTAGE	.50W
DIMMER	N/A
DIMENSIONS	120"L x 0.56"W x 0.7"H
INTEGRATED LED MODULE	10 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
BEAM ANGLE	120°
COLOR RENDERING	90 CRI
LAMP COLOR	2000K-6000K Tunable White
LUMENS/WATT	457.20
LUMINOUS FLUX	2286 lumens



Shown in white



Bends Right to Left or Left to Right



CLICK TO VIEW PRODUCT

Notes: