

Lightology

lightology.com
866-954-4489
12-28-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **JUN110995**
Approved On: _____ Approved By: _____

IC20RLEDG4 5 In 600 Lumen IC Remodel Housing 120V

By Juno Lighting



Description

5 Inch 120 Volt 600 Lumen Generation 4 LED IC Remodel Housing is a dedicated LED, Air-Loc sealed remodel housing with integral light engine. Shallow housing allows for fit in 2 x 6 construction. IC remodel housing can be completely covered with insulation. For remodel applications where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Fully sealed housing stops infiltration and exfiltration of air reducing heating and air cooling costs without the use of additional gaskets. Replaceable light engine mounts directly to housing and incorporates the latest generation high lumen output LED array. Comparable light output to 65 watt BR30 incandescent while consuming less than 11.5 watts. Available with 2700K, 3000K, 3500K, or 4100K color temperature, 90 minimum CRI. Wide flood distribution shipped as standard. Optional optic accessories available, sold separately. 120 volt only driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers (see attached manufacturer dimmer compatibility reference). Title 24 compliant with select trims. Note: A complete fixture requires a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	11.5W
DIMMER	Dimmable
DIMENSIONS	13.5"L x 5.9"W x 4.9"H
INTEGRATED LED MODULE	1 x LED/11.5W/120V LED

Technical Information

HOUSING HEIGHT	5"
HOUSING TYPE	Remodel IC
CEILING TYPE	Drywall with Trim
BEAM ANGLE	50000°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	52.17
LUMINOUS FLUX	600 lumens



Shown in aluminum



5 1/2" CEILING CUTOUT



CLICK TO VIEW PRODUCT

Notes: