

lightology.com 866-954-4489 10-16-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1116060	
Approved On:	Approved By:

Vanishing Point Tubo LG Downlight-Millwork 24V/Remote Power By PureEdge Lighting







Description

The Vanishing Point Tubo Large Downlight integrates with the Vanishing Point Plaster-In-System for use in millwork applications. Features a .5 inch opening with no visible canopy line -- just the small .5 inch point of connection where the fixture stem disappears into the ceiling. Up to 10 fixtures can be fed using the remote universal power supply. Available in a variety of color temperature options, including Warm Dim 3000K-1800K, offered in multiple beam spread options that can be changed in the field. 2400K, 2700K, 3000K, 3500K, and Warm Dim available in Spot (20 degree), Narrow Flood (35 degree), and Flood (45 degree) beam angle options. Note: A 24VDC remote Universal power supply is required and sold separately. Universal power supply dimmable with ELV/TRIAC/0-10V.Note: Title 24 compliant when used with a Universal power supply and 2700K color temperature.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 1 x LED/14W/24V LED

Technical Information

LAMP LIFE .															(5O	00	0 h	οL	ırs	
BEAM ANGLE																			2	0°	
COLOR RENDE	ERIN	1C																92	2 C	RI	
LAMP COLOR																		27	700	ΣK	
LUMENS/WAT	Τ.																		65.	.71	
LUMINOUS FL	UX															92	20	lun	ne	ns	



Shown in black





CLICK TO VIEW PRODUCT

Notes:			