Lightology

lightology.com
866-954-4489
10-30-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1117885**

Approved On: Approved By:

Vanishing Point Radiant Medium for Drywall 24V/Remote Power


By PureEdge Lighting

Description

The Vanishing Point Radiant Medium integrates with the Vanishing Point Plaster-In-System for use in drywall applications. Features a .5 inch opening with no visible canopy line -- just the small .5 inch point of connection where the fixture stem disappears into the ceiling. Radiant heat sink swivels 90 degrees vertically and 360 degrees horizontally.Available in a variety of color temperature options, including Warm Dim (3000K-1800K), offered in multiple beam spread options that can be changed in the field: Spot (20 degree), Narrow Flood (35 degree), Flood (45 degree), and Wide Flood (60 degree) beam angle options. You may feed up to to 9 Radiant medium fixtures with a single 24VDC remote Universal power supply (power supply required and sold separately). Universal power supply dimmable with ELV/TRIAC/0-10V. Note: Required remote power supply sold separately.



Shown in white



Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	11W
DIMMER	Low Voltage Electronic
DIMENSIONS	1.96"W x 2.83"H
INTEGRATED LED MODULE	1 x LED/11W/24V LED

Technical Information

LAMP LIFE	60000 hours
BEAM ANGLE	20°
COLOR RENDERING	97 CRI
LAMP COLOR	2400K
LUMENS/WATT	76.91
LUMINOUS FLUX	846 lumens

CLICK TO VIEW PRODUCT

Notes: