

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1117925	
Approved On:	Approved By:

Vanishing Point Tubo Large for Drywall 24V/Remote Power By PureEdge Lighting





Description

The Vanishing Point Tubo Large integrates with the Vanishing Point Plaster-In-System for use in drywall applications. Features a .5 inch opening with no visible canopy line -- just the small .5 inch point of connection where the fixture stem disappears into the ceiling. Available in a variety of color temperature options offered in multiple beam spread options that can be changed in the field: 2400K, 2700K, 3000K and 3500K available in Narrow Spot (10 degree), Spot (20 degree), Narrow Flood (35 degree), Flood (45 degree), and Very Wide Flood (75 degree) beam angle options. Note For 7 degree use STB16-BK snoot with NS beam spread.Warm Dim available in Spot (20 degree), Narrow Flood (35 degree), and Flood (45 degree) only. You may feed up to to 6 Tubo large fixtures with a single 24VDC remote Universal power supply (power supply required and sold separately). Universal power supply dimmable with ELV/TRIAC/0-10V. Required remote power supply sold separately. Title 24 compliant when used with 2700K color temperature and a Universal power supply.Product is built to order.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 1x LED/14W/24V LED

Technical Information

LAMP LIFE .														6	OC	000	hc	our	S
BEAM ANGLE																		10	0
COLOR REND	ERINC	ì.															97	CF	١
LAMP COLOR																	240	00	Κ
LUMENS/WAT	т																. 7	3.7	7
LUMINOUS FL	UX .													. 1	103	2 lu	um	en	s



Shown in white





CLICK TO VIEW PRODUCT

Notes:		