



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting



DESCRIPTION

Stomp Strip 24VDC Tunable White is highly durable and designed to withstand damage from stomping and twisting on a job site. 24V, 120-277V input. Field cuttable. Industrial 3M tape lined strip for self adhesion to most smooth, finished surfaces. Compatible for use with all PureEdge 5/8 inch drywall BIY channels including Truline, Reveal and Verge. Tunable White allows for independent control of color temperatures and dimming. Note: Sold in 1 foot increments up to 40 feet 2W (2.5 watts per foot), up to 20 feet 5W (4.6 watts per foot), up to 12 feet 7W (7.3 watts per foot), or up to 10 feet 10W (9.6 watts per foot) with 27K6 Tunable White (2700K-6500K) or 2K6K Tunable White (2000K-6500K) color temperature. Available in following configurations: PIN Connector (PIN) 6 Foot Soldered Lead/1 End (SE1) 6 Foot Soldered Leads/2 Ends (SE2) Note: A DMX color changing power supply or 2XK 0-10V 2-Channel power supply is required and sold separately. 0-10V requires two dimmers --one for intensity and one for color temperature. DMX power supply must be used with PureEdge controller (CDMX1-2XK).



Shown in: Aluminum

SHADE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	2W
DIMMER	0-10V
DIMENSIONS	12"L x 0.4"W
INTEGRATED LED MODULE	
LAMP	1 x LED/2W/24V LED
Technical Information	
LUMINOUS FLUX	360 lumens
LUMENS/WATT	180.00
LAMP COLOR	2000K-6000K Tunable White
COLOR RENDERING	92 CRI
SPEC #	EDG1142293



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE