Lightology

lightology.com
866-954-4489
10-30-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1143878**

Approved On: Approved By:

Soft Strip RGB with PIN or Soldered Leads 24V

By PureEdge Lighting

DAMP

Description

Soft Strip is an RGB (Red-Blue-Green) 24VDC field-cuttable single strip designed for use with PureEdge BIY (build-it-yourself) or DIY (do-it-yourself) systems. Sold in one foot increments with 3 or 5 watts per foot. 3 watt (2.6 watts per foot) allows for a maximum length of 36 feet, or 5 watt (4.4 watts per foot) up to 20 feet. Connector options include:PIN: Pin connectorSE1: 6 foot soldered lead (1 end)SE2: 6 foot soldered lead (2 ends).RGB Soft Strip requires a 24 volt DC power supply with integrated RGB DMX driver. DMX power supply must be used with PureEdge CDMX1-RGBW controller.Note: Light Channel, RGB power supply, controller, power feed, and optional accessories sold separately.



Shown in aluminum

Specifications

COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	3W
DIMMER	N/A
DIMENSIONS	12"L x 0.5"W
INTEGRATED LED MODULE	1 x LED/3W/24V LED

Technical Information

LAMP LIFE	50000 hours
LAMP COLOR	RGB

CLICK TO VIEW PRODUCT

Notes: