Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1144856**

Approved On: Approved By:

Soft Strip RGB+2000K with Pin or Soldered Leads 24V


By PureEdge Lighting

Description

SS6 RGB+2000K Soft Strip with Pin or Soldered Lead connector provides dynamic color effects with red, green, blue + 2000K color temperature white. This color changing strip offers a balanced output of millions of colors and pure white.Sold in 1 foot increments at 6.3 watts per foot up to 16 feet with cutting increments every 3 inches. Self-adhering SS6 mounts to most smooth finished surfaces with industrial strength 3M tape (provided on back of strip). Some unfinished surfaces may require screw-in mounting clips (SS-MCL), sold separately.SS6 Soft Strip requires a 24 volt DC power supply with integrated RGB DMX driver. DMX power supply must be used with PureEdge CDMX1-RGBW controller.Connector options include:PIN: Pin connectorSE1: 6 foot soldered lead (1 end)SE2: 6 foot soldered lead (2 ends)Note: Required system, power supply, power connector (SS-CFX), controller, and optional accessories sold separately.



Shown in aluminum



Specifications

COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	6.3W
DIMMER	N/A
DIMENSIONS	12"L x 0.47"W
INTEGRATED LED MODULE	1 x LED/6.3W/24V LED

Technical Information

LAMP LIFE	50000 hours
LAMP COLOR	RGB
LUMENS/WATT	60.00
LUMINOUS FLUX	378 lumens

CLICK TO VIEW PRODUCT

Notes: