

lightology.com 866-954-4489 10-19-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: CSL1160422	
Approved On:	Approved By:

ECO 1IN Shallow New Construction IC Housing By CSL













Description

The ECO 1 Inch Shallow New Construction Housing is ready to install into 2.5 inch shallow plenums in drywall or T-bar grid ceilings with IC, Airtight and Chicago Plenum certifications. Features a 120V phase control driver offering 5%-100% TRIAC or ELV dimming and delivering up to 1100 lumens. Available in three color temperature options and Warm Dim (3000K-1800K) which visually warms the space as the lights are dimmed. ECO 1 includes a fixed 50 degree optic for general task and accent lighting with minimal glare. Insert up to two lenses for additional light control, sold separately. ECO 1 pairs with a variety of trim styles and colors (round and square, with flange and flangeless) for a clean ceiling aesthetic. Rated for wet locations when used with a wet location trim.Warm Dim with 10, 30, or 50 degree optic requires an MP (Solite Lens). Warm Dim with 80 degree optic requires an FR (Frosted Lens), sold separately.Note: A complete fixture requires a housing, trim, (and mud-in plate for flangeless), sold separately.

Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE
COLINTRY OF ORIGIN China

Technical Information

HOUSING HEIGHT
HOUSING TYPE
LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in black





CLICK TO VIEW PRODUCT

Notes:		