

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: CSL1160429	
Approved On:	Approved By:

ECO 3IN Adjustable New Construction Housing By CSL











Description

The ECO 3 Inch Adjustable New Construction Housing is offered in an IC Airtight rated and Non-IC rated option and fits into drywall or T-bar grid ceiling spaces. Adjustable 0 to 45 degree tilt with 360 degree rotation. Includes tilt angle indicator to provide easy and accurate aiming. Features 120V-277V driver offering 5%-100% TRIAC or ELV dimming and delivering up to 1226 lumens. Available in three color temperature options. ECO 3 includes a 50 degree optic for general task and accent lighting with minimal glare. Insert up to two lenses for additional light control, sold separately. ECO 3 pairs with a variety of trim styles and colors (round and square, standard and flangeless) for a clean ceiling aesthetic. Rated for wet locations when used with a wet location trim. Note: A complete fixture requires a housing, trim (and mud-in plate for flangeless), sold separately.

Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 1x LED/12W/120-277V LED
COUNTRY OF ORIGIN

Technical Information

HOUSING HEIGHT
HOUSING TYPE New Construction NON IC
LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in black



ANC* (Adi New Construction)



CLICK TO VIEW PRODUCT

Notes:			