

lightology.com 866-954-4489 08-05-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>OKT1165649</b>	
Approved On:	Approved By:

## Air Surface Color/Wattage Select Surface Mount Panel By OKT Lighting





## Description


The Air Surface Color/Wattage-Select Surface Mount Panel delivers evenly distributed illumination with its edge-lit LED technology, ideal for offices, retail environments and other commercial applications or healthcare settings. At only 0.68 inches thick, this light maintains an ultra-thin profile for a clean aesthetic. An internal driver is included. Compatible with multiple junction box sizes: 3 inch octagon, 4 inch octagon, 4 inch round and 4 inch square. Color temperature (CCT) can be set to 3000K, 4000K, or 5000K. For the 1 x 4 ft and 2 x 2 ft lights, wattage can be set to 30W, 30W, or 40W. The 2 x 4 ft light can be set to 30W, 40W, or 50W.

## Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE

## Technical Information

LAMP LIFE												50000 hours
COLOR RENDERING												80 CRI
LAMP COLOR												CCT Select
LUMENS/WATT												110.00
LUMINOUS FLUX .												4400 lumens



Shown in alpine white





**CLICK TO VIEW PRODUCT** 

_	
Notes: I	
1000.	