

Lightology

lightology.com
866-954-4489
04-19-26


Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **OKT1165649**
 Approved On: _____ Approved By: _____

Air Surface Color/Wattage Select Surface Mount Panel By OKT Lighting




Description

The Air Surface Color/Wattage-Select Surface Mount Panel delivers evenly distributed illumination with its edge-lit LED technology, ideal for offices, retail environments and other commercial applications or healthcare settings. At only 0.68 inches thick, this light maintains an ultra-thin profile for a clean aesthetic. An internal driver is included. Compatible with multiple junction box sizes: 3 inch octagon, 4 inch octagon, 4 inch round and 4 inch square. Color temperature (CCT) can be set to 3000K, 4000K, or 5000K. For the 1 x 4 ft and 2 x 2 ft lights, wattage can be set to 20W, 30W, or 40W. The 2 x 4 ft light can be set to 30W, 40W, or 50W.



Shown in alpine white



Specifications

COLOR	N/A
BODY FINISH	Alpine White
WATTAGE	40W
DIMMER	0-10V
DIMENSIONS	23.7"L x 23.7"W x 0.68"H
INTEGRATED LED MODULE	1 x LED/40W/120-277V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	80 CRI
LAMP COLOR	CCT Select
LUMENS/WATT	110.00
LUMINOUS FLUX	4400 lumens



CLICK TO VIEW PRODUCT

Notes: