

lightology.com 866-954-4489 10-17-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: OKT1165649	
Approved On:	Approved By:

Air Surface Color/Wattage Select Surface Mount Panel By OKT Lighting





Description


The Air Surface Color/Wattage-Select Surface Mount Panel delivers evenly distributed illumination with its edge-lit LED technology, ideal for offices, retail environments and other commercial applications or healthcare settings. At only 0.68 inches thick, this light maintains an ultra-thin profile for a clean aesthetic. An internal driver is included. Compatible with multiple junction box sizes: 3 inch octagon, 4 inch octagon, 4 inch round and 4 inch square. Color temperature (CCT) can be set to 3000K, 4000K, or 5000K. For the 1 x 4 ft and 2 x 2 ft lights, wattage can be set to 20W, 30W, or 40W. The 2 x 4 ft light can be set to 30W, 40W, or 50W.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE	 											50000 hours
COLOR RENDERING	 											80 CRI
LAMP COLOR	 											CCT Select
LUMENS/WATT	 											110.00
LUMINOUS FLUX .												4400 lumens



Shown in alpine white





CLICK TO VIEW PRODUCT

Notes:			