

Lightology

lightology.com
866-954-4489
04-21-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **HIN1189107**

Approved On: _____ Approved By: _____

LumaCore Variable Output 12V Shielded Well Light By Hinkley Lighting



Description

The LumaCore Variable Output 12V LED Shielded Well Light is made of aluminum and complemented by a Clear lens. Choice of 2700K or 3000K color temperatures with variable wattage settings of 3W - 260 lumens, 5W - 350 lumens or 8W - 750 lumens. Three lens options, 20 degree spot, 40 degree flood, and 60 degree flood, are included to offer versatility in beam spread via an easy to remove and insert optic assembly. Lamp adjustable +/- 20 degrees. PVC constructed concrete pour kit, burial sleeve, and wiring kit is supplied. Includes a dense foam cap to prevent concrete from entering. Note: Required 12V low voltage magnetic transformer sold separately.

Specifications

COLOR Clear
BODY FINISH Matte Bronze
WATTAGE 12W
DIMMER Not Dimmable
DIMENSIONS 4.5"W x 5"H
INTEGRATED LED MODULE 1 x LED/12W/12V LED
COUNTRY OF ORIGIN China

Technical Information

LAMP LIFE 40000 hours
COLOR RENDERING 80 CRI
LAMP COLOR 2700K
LUMENS/WATT 62.50
LUMINOUS FLUX 750 lumens



Shown in matte bronze / clear



CLICK TO VIEW PRODUCT

Notes: